

# Technische Daten

Ausdruck vom 19. Sep. 16

Heizkörper der Firma: EN442 CARADON STELRAD 2016/09

Datensatz vom 19. Sep. 16

	Typ	Bauhöhe	Bautiefe	Länge	Reg.-Nr.	Leistung	Exponent	Gewicht	Fläche	Inhalt	Zeta
<b>Almada</b>											
	<b>Erstellt am 19. Sep. 16</b>										
	Almada	1186 mm	50 mm	450 mm	-----	660,7 W	1,250	14,10 kg	1,320 m <sup>2</sup>	5,200 l	-----
	Almada	1186 mm	50 mm	600 mm	-----	860,8 W	1,230	17,62 kg	1,650 m <sup>2</sup>	6,150 l	-----
	Almada	1511 mm	50 mm	600 mm	-----	1079,4 W	1,230	21,94 kg	2,080 m <sup>2</sup>	7,550 l	-----
	Almada	1511 mm	50 mm	450 mm	-----	828,7 W	1,240	17,60 kg	1,650 m <sup>2</sup>	6,300 l	-----
	Almada	1771 mm	50 mm	600 mm	-----	1254,6 W	1,230	26,07 kg	2,480 m <sup>2</sup>	9,150 l	-----
	Almada	1771 mm	50 mm	450 mm	-----	966,9 W	1,240	20,98 kg	1,970 m <sup>2</sup>	7,640 l	-----
<b>Bratan</b>											
	<b>Erstellt am 19. Sep. 16</b>										
	Bratan	1800 mm	52 mm	751 mm	-----	2381,8 W	1,330	68,20 kg	5,660 m <sup>2</sup>	32,000 l	-----
	Bratan	1800 mm	52 mm	635 mm	-----	2015,2 W	1,330	57,70 kg	4,780 m <sup>2</sup>	27,100 l	-----
	Bratan	1800 mm	52 mm	403 mm	-----	1283,2 W	1,330	36,70 kg	3,040 m <sup>2</sup>	17,200 l	-----
	Bratan	1800 mm	52 mm	519 mm	-----	1649,8 W	1,330	47,20 kg	3,920 m <sup>2</sup>	22,100 l	-----
	Bratan	2000 mm	52 mm	751 mm	-----	2480,5 W	1,310	75,70 kg	6,270 m <sup>2</sup>	35,300 l	-----
	Bratan	2000 mm	52 mm	519 mm	-----	1717,1 W	1,310	52,40 kg	4,340 m <sup>2</sup>	24,400 l	-----
	Bratan	2000 mm	52 mm	403 mm	-----	1335,3 W	1,310	40,80 kg	3,370 m <sup>2</sup>	19,000 l	-----
	Bratan	2000 mm	52 mm	635 mm	-----	2098,8 W	1,310	64,10 kg	5,310 m <sup>2</sup>	29,900 l	-----
<b>Bratan 180</b>											
	<b>Erstellt am 19. Sep. 16</b>										
	Bratan 180	1800 mm	170 mm	309 mm	-----	1141,8 W	1,300	34,40 kg	2,770 m <sup>2</sup>	16,100 l	-----
	Bratan 180	1800 mm	188 mm	351 mm	-----	1463,8 W	1,300	40,30 kg	3,190 m <sup>2</sup>	18,400 l	-----
	Bratan 180	2000 mm	170 mm	309 mm	-----	1570,9 W	1,310	38,30 kg	3,070 m <sup>2</sup>	17,800 l	-----
	Bratan 180	2000 mm	188 mm	351 mm	-----	1831,7 W	1,310	44,70 kg	3,540 m <sup>2</sup>	20,300 l	-----

	Typ	Bauhöhe	Bautiefe	Länge	Reg.-Nr.	Leistung	Exponent	Gewicht	Fläche	Inhalt	Zeta
<b>Bratan 90</b>											<b>Erstellt am 19. Sep. 16</b>
	Bratan 90	1800 mm	294 mm	276 mm	-----	1659,9 W	1,300	35,20 kg	2,770 m <sup>2</sup>	16,000 l	-----
	Bratan 90	2000 mm	294 mm	276 mm	-----	1777,5 W	1,290	38,50 kg	3,070 m <sup>2</sup>	17,800 l	-----
<b>Briza Double</b>											<b>Erstellt am 19. Sep. 16</b>
	Double	1800 mm	80 mm	521 mm	-----	2197,3 W	1,340	33,50 kg	1,460 m <sup>2</sup>	16,200 l	-----
	Double	1800 mm	80 mm	447 mm	-----	1890,3 W	1,350	28,80 kg	1,190 m <sup>2</sup>	13,800 l	-----
	Double	1800 mm	80 mm	669 mm	-----	2814,2 W	1,330	43,00 kg	2,120 m <sup>2</sup>	20,800 l	-----
	Double	1800 mm	80 mm	595 mm	-----	2508,8 W	1,340	38,30 kg	1,770 m <sup>2</sup>	18,500 l	-----
	Double	2000 mm	80 mm	595 mm	-----	2777,3 W	1,340	42,30 kg	1,820 m <sup>2</sup>	20,400 l	-----
	Double	2000 mm	80 mm	521 mm	-----	2435,9 W	1,350	37,00 kg	1,510 m <sup>2</sup>	17,800 l	-----
	Double	2000 mm	80 mm	669 mm	-----	3121,8 W	1,340	47,60 kg	2,170 m <sup>2</sup>	23,000 l	-----
	Double	2000 mm	80 mm	447 mm	-----	2094,5 W	1,360	31,80 kg	1,240 m <sup>2</sup>	15,300 l	-----
<b>Briza Single</b>											<b>Erstellt am 19. Sep. 16</b>
	Single	1800 mm	59 mm	595 mm	-----	1583,9 W	1,280	20,00 kg	1,100 m <sup>2</sup>	9,800 l	-----
	Single	1800 mm	59 mm	447 mm	-----	1181,7 W	1,280	15,10 kg	0,810 m <sup>2</sup>	7,300 l	-----
	Single	1800 mm	59 mm	521 mm	-----	1383,4 W	1,280	17,60 kg	0,940 m <sup>2</sup>	8,600 l	-----
	Single	1800 mm	59 mm	669 mm	-----	1782,5 W	1,270	22,50 kg	1,280 m <sup>2</sup>	11,000 l	-----
	Single	2000 mm	59 mm	447 mm	-----	1317,0 W	1,280	16,60 kg	0,860 m <sup>2</sup>	8,100 l	-----
	Single	2000 mm	59 mm	521 mm	-----	1542,6 W	1,280	19,30 kg	0,990 m <sup>2</sup>	9,400 l	-----
	Single	2000 mm	59 mm	595 mm	-----	1768,1 W	1,280	22,00 kg	1,150 m <sup>2</sup>	10,800 l	-----
	Single	2000 mm	59 mm	669 mm	-----	1993,7 W	1,280	24,80 kg	1,320 m <sup>2</sup>	12,100 l	-----
<b>Carissa</b>											<b>Erstellt am 19. Sep. 16</b>
	Carissa	1199 mm	75 mm	595 mm	-----	979,3 W	1,190	13,52 kg	1,470 m <sup>2</sup>	7,070 l	-----
	Carissa	1791 mm	75 mm	595 mm	-----	1433,3 W	1,210	20,43 kg	2,200 m <sup>2</sup>	10,540 l	-----
	Carissa	2013 mm	75 mm	595 mm	-----	1601,7 W	1,210	23,35 kg	2,510 m <sup>2</sup>	12,050 l	-----

	Typ	Bauhöhe	Bautiefe	Länge	Reg.-Nr.	Leistung	Exponent	Gewicht	Fläche	Inhalt	Zeta
<b>Compact</b>									<b>Erstellt am 19. Sep. 16</b>		
	Typ 22	300 mm	100 mm	1000 mm	-----	1241,4 W	1,330	16,80 kg	3,510 m <sup>2</sup>	3,700 l	-----
	Typ 33	300 mm	158 mm	1000 mm	-----	1699,4 W	1,310	25,20 kg	5,260 m <sup>2</sup>	5,400 l	-----
	Typ 11	400 mm	61 mm	1000 mm	-----	851,6 W	1,310	12,78 kg	2,950 m <sup>2</sup>	2,340 l	-----
	Typ 22	400 mm	100 mm	1000 mm	-----	1573,9 W	1,330	22,87 kg	4,920 m <sup>2</sup>	4,670 l	-----
	Typ 33	400 mm	158 mm	1000 mm	-----	2159,3 W	1,320	34,30 kg	7,380 m <sup>2</sup>	6,870 l	-----
	Typ 11	500 mm	61 mm	1000 mm	-----	1047,5 W	1,300	16,24 kg	3,800 m <sup>2</sup>	2,800 l	-----
	Typ 21	500 mm	77 mm	1000 mm	-----	1460,2 W	1,340	24,63 kg	4,310 m <sup>2</sup>	5,630 l	-----
	Typ 22	500 mm	100 mm	1000 mm	-----	1888,7 W	1,330	28,93 kg	6,330 m <sup>2</sup>	5,630 l	-----
	Typ 33	500 mm	158 mm	1000 mm	-----	2594,7 W	1,320	43,40 kg	9,490 m <sup>2</sup>	8,330 l	-----
	Typ 11	600 mm	61 mm	1000 mm	-----	1230,2 W	1,290	19,70 kg	4,660 m <sup>2</sup>	3,250 l	-----
	Typ 21	600 mm	77 mm	1000 mm	-----	1703,4 W	1,340	29,80 kg	5,240 m <sup>2</sup>	6,600 l	-----
	Typ 22	600 mm	100 mm	1000 mm	-----	2189,6 W	1,330	35,00 kg	7,740 m <sup>2</sup>	6,600 l	-----
	Typ 33	600 mm	158 mm	1000 mm	-----	3014,9 W	1,320	52,50 kg	11,610 m <sup>2</sup>	9,800 l	-----
	Typ 11	700 mm	61 mm	1000 mm	-----	1402,2 W	1,290	22,90 kg	5,510 m <sup>2</sup>	3,770 l	-----
	Typ 21	700 mm	77 mm	1000 mm	-----	1937,7 W	1,340	34,50 kg	6,180 m <sup>2</sup>	7,630 l	-----
	Typ 22	700 mm	100 mm	1000 mm	-----	2483,5 W	1,340	40,53 kg	9,150 m <sup>2</sup>	7,630 l	-----
	Typ 33	700 mm	158 mm	1000 mm	-----	3434,6 W	1,340	60,77 kg	13,720 m <sup>2</sup>	11,370 l	-----
	Typ 11	900 mm	61 mm	1000 mm	-----	1707,2 W	1,290	29,30 kg	7,220 m <sup>2</sup>	4,800 l	-----
	Typ 21	900 mm	77 mm	1000 mm	-----	2384,7 W	1,340	43,90 kg	8,050 m <sup>2</sup>	9,700 l	-----
	Typ 22	900 mm	100 mm	1000 mm	-----	3038,5 W	1,350	51,60 kg	11,970 m <sup>2</sup>	9,700 l	-----
	Typ 33	900 mm	158 mm	1000 mm	-----	4244,8 W	1,370	77,30 kg	17,960 m <sup>2</sup>	14,500 l	-----
<b>Compact All In</b>									<b>Erstellt am 19. Sep. 16</b>		
	Typ 11	300 mm	61 mm	1000 mm	-----	642,4 W	1,320	9,31 kg	2,090 m <sup>2</sup>	1,890 l	-----
	Typ 21	300 mm	77 mm	1000 mm	-----	941,9 W	1,330	14,29 kg	2,440 m <sup>2</sup>	3,700 l	-----
	Typ 22	300 mm	100 mm	1000 mm	-----	1241,5 W	1,330	16,80 kg	3,510 m <sup>2</sup>	3,700 l	-----
	Typ 33	300 mm	158 mm	1000 mm	-----	1699,5 W	1,310	25,20 kg	5,260 m <sup>2</sup>	5,400 l	-----

Typ	Bauhöhe	Bautiefe	Länge	Reg.-Nr.	Leistung	Exponent	Gewicht	Fläche	Inhalt	Zeta
Typ 11	400 mm	61 mm	1000 mm	-----	851,6 W	1,310	12,78 kg	2,950 m <sup>2</sup>	2,340 l	-----
Typ 21	400 mm	77 mm	1000 mm	-----	1206,1 W	1,330	19,46 kg	3,370 m <sup>2</sup>	4,670 l	-----
Typ 22	400 mm	100 mm	1000 mm	-----	1574,0 W	1,330	22,87 kg	4,920 m <sup>2</sup>	4,670 l	-----
Typ 33	400 mm	158 mm	1000 mm	-----	2159,3 W	1,320	34,30 kg	7,380 m <sup>2</sup>	6,870 l	-----
Typ 11	500 mm	61 mm	1000 mm	-----	1047,6 W	1,300	16,24 kg	3,800 m <sup>2</sup>	2,800 l	-----
Typ 21	500 mm	77 mm	1000 mm	-----	1460,2 W	1,340	24,63 kg	4,310 m <sup>2</sup>	5,630 l	-----
Typ 22	500 mm	100 mm	1000 mm	-----	1888,8 W	1,330	28,93 kg	6,330 m <sup>2</sup>	5,630 l	-----
Typ 33	500 mm	158 mm	1000 mm	-----	2594,7 W	1,320	43,40 kg	9,490 m <sup>2</sup>	8,330 l	-----
Typ 11	600 mm	61 mm	1000 mm	-----	1230,3 W	1,290	19,70 kg	4,660 m <sup>2</sup>	3,250 l	-----
Typ 21	600 mm	77 mm	1000 mm	-----	1703,4 W	1,340	29,80 kg	5,240 m <sup>2</sup>	6,600 l	-----
Typ 22	600 mm	100 mm	1000 mm	-----	2189,7 W	1,330	35,00 kg	7,740 m <sup>2</sup>	6,600 l	-----
Typ 33	600 mm	158 mm	1000 mm	-----	3015,0 W	1,320	52,50 kg	11,610 m <sup>2</sup>	9,800 l	-----
Typ 11	700 mm	61 mm	1000 mm	-----	1402,2 W	1,290	22,90 kg	5,510 m <sup>2</sup>	3,770 l	-----
Typ 21	700 mm	77 mm	1000 mm	-----	1937,7 W	1,340	34,50 kg	6,180 m <sup>2</sup>	7,630 l	-----
Typ 22	700 mm	100 mm	1000 mm	-----	2483,6 W	1,340	40,53 kg	9,150 m <sup>2</sup>	7,630 l	-----
Typ 33	700 mm	158 mm	1000 mm	-----	3434,7 W	1,340	60,77 kg	13,720 m <sup>2</sup>	11,370 l	-----
Typ 11	900 mm	61 mm	1000 mm	-----	1707,3 W	1,290	29,30 kg	7,220 m <sup>2</sup>	4,800 l	-----
Typ 21	900 mm	77 mm	1000 mm	-----	2384,8 W	1,340	43,90 kg	8,050 m <sup>2</sup>	9,700 l	-----
Typ 22	900 mm	100 mm	1000 mm	-----	3038,6 W	1,350	51,60 kg	11,970 m <sup>2</sup>	9,700 l	-----
Typ 33	900 mm	158 mm	1000 mm	-----	4244,8 W	1,370	77,30 kg	17,960 m <sup>2</sup>	14,500 l	-----

**Compact Planar**

**Erstellt am 19. Sep. 16**

22	300 mm	102 mm	1000 mm	-----	1168,2 W	1,300	19,60 kg	3,510 m <sup>2</sup>	3,700 l	-----
33	300 mm	160 mm	1000 mm	-----	1695,6 W	1,310	28,00 kg	5,260 m <sup>2</sup>	5,400 l	-----
21	400 mm	79 mm	1000 mm	-----	1121,9 W	1,320	22,87 kg	3,370 m <sup>2</sup>	4,670 l	-----
22	400 mm	102 mm	1000 mm	-----	1480,1 W	1,300	26,40 kg	4,920 m <sup>2</sup>	4,670 l	-----
33	400 mm	160 mm	1000 mm	-----	2132,8 W	1,320	38,13 kg	7,380 m <sup>2</sup>	6,870 l	-----
21	500 mm	79 mm	1000 mm	-----	1340,2 W	1,320	28,89 kg	4,310 m <sup>2</sup>	5,630 l	-----

Typ	Bauhöhe	Bautiefe	Länge	Reg.-Nr.	Leistung	Exponent	Gewicht	Fläche	Inhalt	Zeta
22	500 mm	102 mm	1000 mm	-----	1777,5 W	1,310	33,20 kg	6,330 m <sup>2</sup>	5,630 l	-----
33	500 mm	160 mm	1000 mm	-----	2549,9 W	1,330	48,27 kg	9,490 m <sup>2</sup>	8,330 l	-----
21	600 mm	79 mm	1000 mm	-----	1548,4 W	1,320	34,90 kg	5,240 m <sup>2</sup>	6,600 l	-----
22	600 mm	102 mm	1000 mm	-----	2062,1 W	1,320	40,00 kg	7,740 m <sup>2</sup>	6,600 l	-----
33	600 mm	160 mm	1000 mm	-----	2953,4 W	1,340	58,40 kg	11,610 m <sup>2</sup>	9,800 l	-----
21	700 mm	79 mm	1000 mm	-----	1750,4 W	1,320	40,91 kg	6,180 m <sup>2</sup>	7,630 l	-----
22	700 mm	102 mm	1000 mm	-----	2336,3 W	1,330	46,80 kg	9,150 m <sup>2</sup>	7,630 l	-----
33	700 mm	160 mm	1000 mm	-----	3339,6 W	1,340	68,53 kg	13,720 m <sup>2</sup>	11,370 l	-----
21	900 mm	79 mm	1000 mm	-----	2129,0 W	1,310	52,94 kg	8,050 m <sup>2</sup>	9,700 l	-----
22	900 mm	102 mm	1000 mm	-----	2855,8 W	1,350	60,40 kg	11,970 m <sup>2</sup>	9,700 l	-----
33	900 mm	160 mm	1000 mm	-----	4084,3 W	1,340	88,80 kg	17,960 m <sup>2</sup>	14,500 l	-----

**Compact Style**

Erstellt am 19. Sep. 16

22	300 mm	102 mm	1000 mm	-----	1129,3 W	1,300	19,30 kg	3,510 m <sup>2</sup>	3,100 l	-----
33	300 mm	160 mm	1000 mm	-----	1618,4 W	1,300	27,60 kg	5,260 m <sup>2</sup>	5,400 l	-----
21	400 mm	79 mm	1000 mm	-----	1094,0 W	1,300	22,60 kg	3,370 m <sup>2</sup>	4,150 l	-----
22	400 mm	102 mm	1000 mm	-----	1449,9 W	1,300	25,67 kg	4,920 m <sup>2</sup>	4,130 l	-----
33	400 mm	160 mm	1000 mm	-----	2077,4 W	1,310	36,63 kg	7,380 m <sup>2</sup>	6,630 l	-----
21	500 mm	79 mm	1000 mm	-----	1305,3 W	1,300	28,00 kg	4,310 m <sup>2</sup>	5,200 l	-----
22	500 mm	102 mm	1000 mm	-----	1748,5 W	1,310	32,03 kg	6,330 m <sup>2</sup>	5,170 l	-----
33	500 mm	160 mm	1000 mm	-----	2497,5 W	1,320	45,67 kg	9,490 m <sup>2</sup>	7,870 l	-----
21	600 mm	79 mm	1000 mm	-----	1506,7 W	1,310	33,60 kg	5,240 m <sup>2</sup>	6,250 l	-----
22	600 mm	102 mm	1000 mm	-----	2016,9 W	1,310	38,40 kg	7,740 m <sup>2</sup>	6,200 l	-----
33	600 mm	160 mm	1000 mm	-----	2877,4 W	1,320	54,70 kg	11,610 m <sup>2</sup>	9,100 l	-----
21	700 mm	79 mm	1000 mm	-----	1700,7 W	1,310	39,20 kg	6,180 m <sup>2</sup>	7,300 l	-----
22	700 mm	102 mm	1000 mm	-----	2266,5 W	1,320	44,70 kg	9,150 m <sup>2</sup>	7,030 l	-----
33	700 mm	160 mm	1000 mm	-----	3227,6 W	1,330	63,60 kg	13,720 m <sup>2</sup>	10,630 l	-----
21	900 mm	79 mm	1000 mm	-----	2081,0 W	1,320	50,60 kg	8,050 m <sup>2</sup>	9,000 l	-----

	Typ	Bauhöhe	Bautiefe	Länge	Reg.-Nr.	Leistung	Exponent	Gewicht	Fläche	Inhalt	Zeta
	22	900 mm	102 mm	1000 mm	-----	2690,6 W	1,320	57,30 kg	11,970 m <sup>2</sup>	8,700 l	-----
	33	900 mm	160 mm	1000 mm	-----	3820,5 W	1,330	81,40 kg	17,960 m <sup>2</sup>	13,700 l	-----
<b>Dahlia</b>											<b>Erstellt am 19. Sep. 16</b>
	Dahlia	775 mm	30 mm	495 mm	-----	457,4 W	1,250	6,00 kg	0,640 m <sup>2</sup>	3,600 l	-----
	Dahlia	775 mm	30 mm	585 mm	-----	530,7 W	1,260	6,89 kg	0,740 m <sup>2</sup>	4,010 l	-----
	Dahlia	775 mm	30 mm	737 mm	-----	648,2 W	1,250	8,40 kg	0,910 m <sup>2</sup>	4,700 l	-----
	Dahlia	1181 mm	30 mm	495 mm	-----	675,5 W	1,260	9,00 kg	0,970 m <sup>2</sup>	5,400 l	-----
	Dahlia	1181 mm	30 mm	737 mm	-----	957,3 W	1,250	12,30 kg	1,370 m <sup>2</sup>	7,100 l	-----
	Dahlia	1181 mm	30 mm	585 mm	-----	781,5 W	1,250	10,23 kg	1,120 m <sup>2</sup>	6,030 l	-----
	Dahlia	1411 mm	30 mm	495 mm	-----	804,1 W	1,260	10,74 kg	1,140 m <sup>2</sup>	6,430 l	-----
	Dahlia	1411 mm	30 mm	585 mm	-----	931,5 W	1,260	12,22 kg	1,310 m <sup>2</sup>	7,190 l	-----
	Dahlia	1411 mm	30 mm	737 mm	-----	1139,3 W	1,250	14,71 kg	1,610 m <sup>2</sup>	8,480 l	-----
	Dahlia	1763 mm	30 mm	737 mm	-----	1429,8 W	1,260	18,40 kg	2,060 m <sup>2</sup>	10,600 l	-----
	Dahlia	1763 mm	30 mm	585 mm	-----	1168,3 W	1,270	15,26 kg	1,680 m <sup>2</sup>	8,970 l	-----
	Dahlia	1763 mm	30 mm	495 mm	-----	1009,5 W	1,270	13,40 kg	1,450 m <sup>2</sup>	8,000 l	-----
	Dahlia	1993 mm	30 mm	495 mm	-----	1144,3 W	1,250	13,60 kg	1,620 m <sup>2</sup>	9,150 l	-----
	Dahlia	1993 mm	30 mm	737 mm	-----	1621,3 W	1,240	18,65 kg	2,290 m <sup>2</sup>	12,250 l	-----
	Dahlia	1993 mm	30 mm	585 mm	-----	1323,9 W	1,240	15,48 kg	1,870 m <sup>2</sup>	10,300 l	-----
<b>Dahlia CT</b>											<b>Erstellt am 19. Sep. 16</b>
	Dahlia CT	775 mm	30 mm	585 mm	-----	530,7 W	1,260	6,89 kg	0,740 m <sup>2</sup>	4,010 l	-----
	Dahlia CT	775 mm	30 mm	495 mm	-----	457,4 W	1,250	6,00 kg	0,640 m <sup>2</sup>	3,600 l	-----
	Dahlia CT	775 mm	30 mm	737 mm	-----	648,2 W	1,250	8,40 kg	0,910 m <sup>2</sup>	4,700 l	-----
	Dahlia CT	1181 mm	30 mm	737 mm	-----	957,3 W	1,250	12,30 kg	1,370 m <sup>2</sup>	7,100 l	-----
	Dahlia CT	1181 mm	30 mm	585 mm	-----	781,5 W	1,250	10,23 kg	1,120 m <sup>2</sup>	6,030 l	-----
	Dahlia CT	1181 mm	30 mm	495 mm	-----	675,5 W	1,260	9,00 kg	0,970 m <sup>2</sup>	5,400 l	-----
	Dahlia CT	1411 mm	30 mm	585 mm	-----	931,5 W	1,260	12,22 kg	1,310 m <sup>2</sup>	7,190 l	-----

Typ	Bauhöhe	Bautiefe	Länge	Reg.-Nr.	Leistung	Exponent	Gewicht	Fläche	Inhalt	Zeta
Dahlia CT	1411 mm	30 mm	495 mm	-----	804,1 W	1,260	10,74 kg	1,140 m <sup>2</sup>	6,430 l	-----
Dahlia CT	1411 mm	30 mm	737 mm	-----	1139,3 W	1,250	14,71 kg	1,610 m <sup>2</sup>	8,480 l	-----
Dahlia CT	1763 mm	30 mm	737 mm	-----	1429,8 W	1,260	18,40 kg	2,060 m <sup>2</sup>	10,600 l	-----
Dahlia CT	1763 mm	30 mm	495 mm	-----	1009,5 W	1,270	13,40 kg	1,450 m <sup>2</sup>	8,000 l	-----
Dahlia CT	1763 mm	30 mm	585 mm	-----	1168,3 W	1,270	15,26 kg	1,680 m <sup>2</sup>	8,970 l	-----
Dahlia CT	1993 mm	30 mm	495 mm	-----	1144,3 W	1,250	13,60 kg	1,620 m <sup>2</sup>	9,150 l	-----
Dahlia CT	1993 mm	30 mm	585 mm	-----	1323,9 W	1,240	15,48 kg	1,870 m <sup>2</sup>	10,300 l	-----
Dahlia CT	1993 mm	30 mm	737 mm	-----	1621,3 W	1,240	18,65 kg	2,290 m <sup>2</sup>	12,250 l	-----

### ECO Galva

Erstellt am 19. Sep. 16

Typ 11	300 mm	61 mm	1000 mm	-----	651,3 W	1,310	8,38 kg	2,090 m <sup>2</sup>	1,890 l	-----
Typ 21	300 mm	77 mm	1000 mm	-----	959,8 W	1,250	13,85 kg	2,440 m <sup>2</sup>	3,450 l	-----
Typ 22	300 mm	100 mm	1000 mm	-----	1200,5 W	1,280	15,50 kg	3,510 m <sup>2</sup>	3,450 l	-----
Typ 33	300 mm	158 mm	1000 mm	-----	1687,5 W	1,270	22,90 kg	5,260 m <sup>2</sup>	5,200 l	-----
Typ 11	400 mm	61 mm	1000 mm	-----	865,5 W	1,310	11,68 kg	2,950 m <sup>2</sup>	2,340 l	-----
Typ 21	400 mm	77 mm	1000 mm	-----	1223,4 W	1,270	18,28 kg	3,370 m <sup>2</sup>	4,620 l	-----
Typ 22	400 mm	100 mm	1000 mm	-----	1521,5 W	1,290	20,55 kg	4,920 m <sup>2</sup>	4,620 l	-----
Typ 33	400 mm	158 mm	1000 mm	-----	2162,9 W	1,280	30,53 kg	7,380 m <sup>2</sup>	6,930 l	-----
Typ 11	500 mm	61 mm	1000 mm	-----	1066,4 W	1,300	14,99 kg	3,800 m <sup>2</sup>	2,800 l	-----
Typ 21	500 mm	77 mm	1000 mm	-----	1473,8 W	1,290	22,72 kg	4,310 m <sup>2</sup>	5,780 l	-----
Typ 22	500 mm	100 mm	1000 mm	-----	1826,0 W	1,300	25,60 kg	6,330 m <sup>2</sup>	5,780 l	-----
Typ 33	500 mm	158 mm	1000 mm	-----	2604,4 W	1,300	38,17 kg	9,490 m <sup>2</sup>	8,670 l	-----
Typ 11	600 mm	61 mm	1000 mm	-----	1255,4 W	1,290	18,30 kg	4,660 m <sup>2</sup>	3,250 l	-----
Typ 21	600 mm	77 mm	1000 mm	-----	1713,3 W	1,310	27,15 kg	5,240 m <sup>2</sup>	6,950 l	-----
Typ 22	600 mm	100 mm	1000 mm	-----	2115,2 W	1,310	30,65 kg	7,740 m <sup>2</sup>	6,950 l	-----
Typ 33	600 mm	158 mm	1000 mm	-----	3007,1 W	1,310	45,80 kg	11,610 m <sup>2</sup>	10,400 l	-----
Typ 11	700 mm	61 mm	1000 mm	-----	1433,6 W	1,290	21,33 kg	5,510 m <sup>2</sup>	3,770 l	-----
Typ 21	700 mm	77 mm	1000 mm	-----	1941,0 W	1,320	31,32 kg	6,180 m <sup>2</sup>	8,120 l	-----

Typ	Bauhöhe	Bautiefe	Länge	Reg.-Nr.	Leistung	Exponent	Gewicht	Fläche	Inhalt	Zeta
Typ 22	700 mm	100 mm	1000 mm	-----	2388,6 W	1,310	35,63 kg	9,150 m <sup>2</sup>	8,120 l	-----
Typ 33	700 mm	158 mm	1000 mm	-----	3374,6 W	1,320	53,18 kg	13,720 m <sup>2</sup>	11,270 l	-----
Typ 11	900 mm	61 mm	1000 mm	-----	1753,7 W	1,290	27,40 kg	7,220 m <sup>2</sup>	4,800 l	-----
Typ 21	900 mm	77 mm	1000 mm	-----	2345,9 W	1,280	39,65 kg	8,050 m <sup>2</sup>	10,450 l	-----
Typ 22	900 mm	100 mm	1000 mm	-----	2891,1 W	1,290	45,60 kg	11,970 m <sup>2</sup>	10,450 l	-----
Typ 33	900 mm	158 mm	1000 mm	-----	3938,9 W	1,230	67,94 kg	17,960 m <sup>2</sup>	13,000 l	-----

**Galva**

Erstellt am 19. Sep. 16

Typ 11	300 mm	61 mm	1000 mm	-----	651,3 W	1,310	8,38 kg	2,090 m <sup>2</sup>	1,890 l	-----
Typ 21	300 mm	77 mm	1000 mm	-----	981,1 W	1,330	13,71 kg	2,440 m <sup>2</sup>	3,700 l	-----
Typ 22	300 mm	100 mm	1000 mm	-----	1279,4 W	1,330	15,90 kg	3,510 m <sup>2</sup>	3,700 l	-----
Typ 33	300 mm	158 mm	1000 mm	-----	1789,5 W	1,320	23,80 kg	5,260 m <sup>2</sup>	5,400 l	-----
Typ 11	400 mm	61 mm	1000 mm	-----	865,5 W	1,310	11,68 kg	2,950 m <sup>2</sup>	2,340 l	-----
Typ 21	400 mm	77 mm	1000 mm	-----	1264,2 W	1,330	18,78 kg	3,370 m <sup>2</sup>	4,670 l	-----
Typ 22	400 mm	100 mm	1000 mm	-----	1619,5 W	1,330	21,83 kg	4,920 m <sup>2</sup>	4,670 l	-----
Typ 33	400 mm	158 mm	1000 mm	-----	2282,0 W	1,330	32,67 kg	7,380 m <sup>2</sup>	6,870 l	-----
Typ 11	500 mm	61 mm	1000 mm	-----	1066,4 W	1,300	14,99 kg	3,800 m <sup>2</sup>	2,800 l	-----
Typ 21	500 mm	77 mm	1000 mm	-----	1529,7 W	1,330	23,84 kg	4,310 m <sup>2</sup>	5,630 l	-----
Typ 22	500 mm	100 mm	1000 mm	-----	1940,6 W	1,330	27,77 kg	6,330 m <sup>2</sup>	5,630 l	-----
Typ 33	500 mm	158 mm	1000 mm	-----	2747,0 W	1,340	41,53 kg	9,490 m <sup>2</sup>	8,330 l	-----
Typ 11	600 mm	61 mm	1000 mm	-----	1255,4 W	1,290	18,30 kg	4,660 m <sup>2</sup>	3,250 l	-----
Typ 21	600 mm	77 mm	1000 mm	-----	1781,3 W	1,330	28,90 kg	5,240 m <sup>2</sup>	6,600 l	-----
Typ 22	600 mm	100 mm	1000 mm	-----	2247,8 W	1,330	33,70 kg	7,740 m <sup>2</sup>	6,600 l	-----
Typ 33	600 mm	158 mm	1000 mm	-----	3189,5 W	1,350	50,40 kg	11,610 m <sup>2</sup>	9,800 l	-----
Typ 11	700 mm	61 mm	1000 mm	-----	1433,6 W	1,290	21,33 kg	5,510 m <sup>2</sup>	3,770 l	-----
Typ 21	700 mm	77 mm	1000 mm	-----	2022,6 W	1,340	33,50 kg	6,180 m <sup>2</sup>	7,630 l	-----
Typ 22	700 mm	100 mm	1000 mm	-----	2546,9 W	1,340	39,13 kg	9,150 m <sup>2</sup>	7,630 l	-----
Typ 33	700 mm	158 mm	1000 mm	-----	3604,4 W	1,350	58,47 kg	13,720 m <sup>2</sup>	11,370 l	-----



	Typ	Bauhöhe	Bautiefe	Länge	Reg.-Nr.	Leistung	Exponent	Gewicht	Fläche	Inhalt	Zeta
	Typ 11	900 mm	61 mm	1000 mm	-----	1753,7 W	1,290	27,40 kg	7,220 m <sup>2</sup>	4,800 l	-----
	Typ 21	900 mm	77 mm	1000 mm	-----	2466,9 W	1,360	42,70 kg	8,050 m <sup>2</sup>	9,700 l	-----
	Typ 22	900 mm	100 mm	1000 mm	-----	3112,1 W	1,350	50,00 kg	11,970 m <sup>2</sup>	9,700 l	-----
	Typ 33	900 mm	158 mm	1000 mm	-----	4390,0 W	1,370	74,60 kg	17,960 m <sup>2</sup>	14,500 l	-----
<b>Gilia Double</b>											<b>Erstellt am 19. Sep. 16</b>
	Double	1199 mm	80 mm	600 mm	-----	1430,9 W	1,220	24,61 kg	2,650 m <sup>2</sup>	12,950 l	-----
	Double	1199 mm	80 mm	500 mm	-----	1196,2 W	1,230	21,14 kg	2,260 m <sup>2</sup>	11,180 l	-----
	Double	1199 mm	80 mm	750 mm	-----	1783,6 W	1,210	29,82 kg	3,230 m <sup>2</sup>	15,590 l	-----
	Double	1791 mm	80 mm	500 mm	-----	1744,6 W	1,240	31,75 kg	3,390 m <sup>2</sup>	16,620 l	-----
	Double	1791 mm	80 mm	600 mm	-----	2074,4 W	1,230	36,94 kg	3,970 m <sup>2</sup>	19,230 l	-----
	Double	1791 mm	80 mm	750 mm	-----	2565,9 W	1,210	44,72 kg	4,850 m <sup>2</sup>	23,130 l	-----
	Double	2013 mm	80 mm	600 mm	-----	2327,8 W	1,230	42,01 kg	4,530 m <sup>2</sup>	22,130 l	-----
	Double	2013 mm	80 mm	750 mm	-----	2872,9 W	1,210	50,82 kg	5,530 m <sup>2</sup>	26,650 l	-----
	Double	2013 mm	80 mm	500 mm	-----	1961,1 W	1,240	36,14 kg	3,870 m <sup>2</sup>	19,110 l	-----
<b>Gilia Single</b>											<b>Erstellt am 19. Sep. 16</b>
	Single	1199 mm	59 mm	750 mm	-----	1194,7 W	1,170	16,14 kg	1,760 m <sup>2</sup>	8,250 l	-----
	Single	1199 mm	59 mm	600 mm	-----	979,3 W	1,190	13,52 kg	1,470 m <sup>2</sup>	7,070 l	-----
	Single	1199 mm	59 mm	500 mm	-----	834,0 W	1,200	11,77 kg	1,280 m <sup>2</sup>	6,290 l	-----
	Single	1791 mm	59 mm	500 mm	-----	1224,8 W	1,230	17,83 kg	1,910 m <sup>2</sup>	9,350 l	-----
	Single	1791 mm	59 mm	600 mm	-----	1433,3 W	1,210	20,43 kg	2,200 m <sup>2</sup>	10,540 l	-----
	Single	1791 mm	59 mm	750 mm	-----	1739,2 W	1,170	24,32 kg	2,640 m <sup>2</sup>	12,330 l	-----
	Single	2013 mm	59 mm	600 mm	-----	1601,7 W	1,210	23,35 kg	2,510 m <sup>2</sup>	12,050 l	-----
	Single	2013 mm	59 mm	750 mm	-----	1949,3 W	1,170	27,79 kg	3,010 m <sup>2</sup>	14,090 l	-----
	Single	2013 mm	59 mm	500 mm	-----	1367,5 W	1,240	20,38 kg	2,180 m <sup>2</sup>	10,680 l	-----
<b>Horta Double</b>											<b>Erstellt am 19. Sep. 16</b>
	Double	1600 mm	156 mm	888 mm	-----	3793,7 W	1,260	88,20 kg	8,370 m <sup>2</sup>	25,200 l	-----

Typ	Bauhöhe	Bautiefe	Länge	Reg.-Nr.	Leistung	Exponent	Gewicht	Fläche	Inhalt	Zeta
Double	1600 mm	156 mm	788 mm	-----	3372,8 W	1,260	78,40 kg	7,440 m <sup>2</sup>	22,400 l	-----
Double	1600 mm	156 mm	688 mm	-----	2950,8 W	1,260	68,60 kg	6,510 m <sup>2</sup>	19,600 l	-----
Double	1600 mm	156 mm	588 mm	-----	2529,9 W	1,260	58,80 kg	5,580 m <sup>2</sup>	16,800 l	-----
Double	1600 mm	156 mm	488 mm	-----	2107,9 W	1,260	49,00 kg	4,650 m <sup>2</sup>	14,000 l	-----
Double	1800 mm	156 mm	888 mm	-----	4289,5 W	1,270	98,10 kg	9,380 m <sup>2</sup>	27,900 l	-----
Double	1800 mm	156 mm	788 mm	-----	3812,9 W	1,270	87,20 kg	8,340 m <sup>2</sup>	24,800 l	-----
Double	1800 mm	156 mm	688 mm	-----	3336,3 W	1,270	76,30 kg	7,300 m <sup>2</sup>	21,700 l	-----
Double	1800 mm	156 mm	488 mm	-----	2383,0 W	1,270	54,50 kg	5,210 m <sup>2</sup>	15,500 l	-----
Double	1800 mm	156 mm	588 mm	-----	2859,7 W	1,270	65,40 kg	6,250 m <sup>2</sup>	18,600 l	-----
Double	2000 mm	156 mm	888 mm	-----	4773,6 W	1,270	108,00 kg	10,390 m <sup>2</sup>	30,600 l	-----
Double	2000 mm	156 mm	788 mm	-----	4243,2 W	1,270	96,00 kg	9,240 m <sup>2</sup>	27,200 l	-----
Double	2000 mm	156 mm	688 mm	-----	3712,8 W	1,270	84,00 kg	8,080 m <sup>2</sup>	23,800 l	-----
Double	2000 mm	156 mm	588 mm	-----	3182,4 W	1,270	72,00 kg	6,930 m <sup>2</sup>	20,400 l	-----
Double	2000 mm	156 mm	488 mm	-----	2652,0 W	1,270	60,00 kg	5,770 m <sup>2</sup>	17,000 l	-----

### Horta Slimline

Erstellt am 19. Sep. 16

Slimline	1600 mm	97 mm	588 mm	-----	1495,6 W	1,330	29,69 kg	2,860 m <sup>2</sup>	9,000 l	-----
Slimline	1600 mm	97 mm	488 mm	-----	1246,5 W	1,330	24,74 kg	2,380 m <sup>2</sup>	7,500 l	-----
Slimline	1600 mm	97 mm	688 mm	-----	1744,7 W	1,330	34,64 kg	3,330 m <sup>2</sup>	10,500 l	-----
Slimline	1600 mm	97 mm	788 mm	-----	1995,0 W	1,330	39,58 kg	3,810 m <sup>2</sup>	12,000 l	-----
Slimline	1600 mm	97 mm	888 mm	-----	2244,0 W	1,330	44,53 kg	4,280 m <sup>2</sup>	13,500 l	-----
Slimline	1800 mm	97 mm	788 mm	-----	2254,0 W	1,320	44,13 kg	4,260 m <sup>2</sup>	13,440 l	-----
Slimline	1800 mm	97 mm	488 mm	-----	1408,4 W	1,320	27,58 kg	2,660 m <sup>2</sup>	8,400 l	-----
Slimline	1800 mm	97 mm	888 mm	-----	2535,4 W	1,320	49,64 kg	4,790 m <sup>2</sup>	15,120 l	-----
Slimline	1800 mm	97 mm	688 mm	-----	1971,3 W	1,320	38,61 kg	3,720 m <sup>2</sup>	11,760 l	-----
Slimline	1800 mm	97 mm	588 mm	-----	1689,8 W	1,320	33,10 kg	3,190 m <sup>2</sup>	10,080 l	-----
Slimline	2000 mm	97 mm	488 mm	-----	1580,0 W	1,320	30,42 kg	2,940 m <sup>2</sup>	9,300 l	-----
Slimline	2000 mm	97 mm	788 mm	-----	2527,8 W	1,320	48,67 kg	4,700 m <sup>2</sup>	14,880 l	-----

Typ	Bauhöhe	Bautiefe	Länge	Reg.-Nr.	Leistung	Exponent	Gewicht	Fläche	Inhalt	Zeta
Slimline	2000 mm	97 mm	688 mm	-----	2212,3 W	1,320	42,59 kg	4,120 m <sup>2</sup>	13,020 l	-----
Slimline	2000 mm	97 mm	588 mm	-----	1895,6 W	1,320	36,50 kg	3,530 m <sup>2</sup>	11,160 l	-----
Slimline	2000 mm	97 mm	888 mm	-----	2844,6 W	1,320	54,76 kg	5,290 m <sup>2</sup>	16,740 l	-----

### Horta vertical

Erstellt am 19. Sep. 16

vertical	1600 mm	50 mm	668 mm	-----	1445,0 W	1,320	26,00 kg	2,420 m <sup>2</sup>	7,800 l	-----
vertical	1600 mm	50 mm	408 mm	-----	867,0 W	1,320	15,70 kg	1,460 m <sup>2</sup>	4,700 l	-----
vertical	1600 mm	50 mm	538 mm	-----	1156,0 W	1,320	20,80 kg	1,940 m <sup>2</sup>	6,300 l	-----
vertical	1600 mm	50 mm	798 mm	-----	1734,0 W	1,320	31,20 kg	2,910 m <sup>2</sup>	9,400 l	-----
vertical	1800 mm	50 mm	538 mm	-----	1294,8 W	1,320	23,20 kg	2,170 m <sup>2</sup>	6,900 l	-----
vertical	1800 mm	50 mm	668 mm	-----	1619,1 W	1,320	29,00 kg	2,710 m <sup>2</sup>	8,600 l	-----
vertical	1800 mm	50 mm	798 mm	-----	1943,5 W	1,320	34,80 kg	3,250 m <sup>2</sup>	10,400 l	-----
vertical	1800 mm	50 mm	408 mm	-----	971,7 W	1,320	17,50 kg	1,630 m <sup>2</sup>	5,200 l	-----
vertical	2000 mm	50 mm	408 mm	-----	1073,9 W	1,320	19,30 kg	1,790 m <sup>2</sup>	5,700 l	-----
vertical	2000 mm	50 mm	538 mm	-----	1431,1 W	1,320	25,60 kg	2,390 m <sup>2</sup>	7,600 l	-----
vertical	2000 mm	50 mm	668 mm	-----	1789,5 W	1,320	32,00 kg	2,990 m <sup>2</sup>	9,500 l	-----
vertical	2000 mm	50 mm	798 mm	-----	2147,9 W	1,320	38,40 kg	3,580 m <sup>2</sup>	11,400 l	-----

### Hygiene

Erstellt am 19. Sep. 16

Typ 10	300 mm	47 mm	1000 mm	-----	423,6 W	1,280	6,17 kg	0,680 m <sup>2</sup>	1,890 l	-----
Typ 20	300 mm	77 mm	1000 mm	-----	723,2 W	1,340	11,64 kg	1,370 m <sup>2</sup>	3,700 l	-----
Typ 30	300 mm	158 mm	1000 mm	-----	1080,3 W	1,300	17,90 kg	2,040 m <sup>2</sup>	5,200 l	-----
Typ 10	400 mm	47 mm	1000 mm	-----	539,8 W	1,290	8,22 kg	0,910 m <sup>2</sup>	2,340 l	-----
Typ 20	400 mm	77 mm	1000 mm	-----	922,9 W	1,330	15,86 kg	1,830 m <sup>2</sup>	4,670 l	-----
Typ 30	400 mm	158 mm	1000 mm	-----	1349,4 W	1,300	23,37 kg	2,730 m <sup>2</sup>	6,570 l	-----
Typ 10	500 mm	47 mm	1000 mm	-----	655,2 W	1,300	10,28 kg	1,140 m <sup>2</sup>	2,800 l	-----
Typ 20	500 mm	77 mm	1000 mm	-----	1114,4 W	1,320	20,08 kg	2,280 m <sup>2</sup>	5,630 l	-----
Typ 30	500 mm	158 mm	1000 mm	-----	1608,8 W	1,310	28,83 kg	3,420 m <sup>2</sup>	7,930 l	-----

Typ	Bauhöhe	Bautiefe	Länge	Reg.-Nr.	Leistung	Exponent	Gewicht	Fläche	Inhalt	Zeta
Typ 10	600 mm	47 mm	1000 mm	-----	768,5 W	1,310	12,33 kg	1,370 m <sup>2</sup>	3,250 l	-----
Typ 20	600 mm	77 mm	1000 mm	-----	1301,1 W	1,320	24,30 kg	2,740 m <sup>2</sup>	6,600 l	-----
Typ 30	600 mm	158 mm	1000 mm	-----	1856,9 W	1,310	34,30 kg	4,110 m <sup>2</sup>	9,300 l	-----
Typ 10	700 mm	47 mm	1000 mm	-----	882,2 W	1,320	14,19 kg	1,600 m <sup>2</sup>	3,770 l	-----
Typ 20	700 mm	77 mm	1000 mm	-----	1481,6 W	1,320	28,00 kg	3,200 m <sup>2</sup>	7,630 l	-----
Typ 30	700 mm	158 mm	1000 mm	-----	2102,5 W	1,320	40,07 kg	4,790 m <sup>2</sup>	10,670 l	-----
Typ 10	900 mm	47 mm	1000 mm	-----	1108,7 W	1,330	17,90 kg	2,060 m <sup>2</sup>	4,800 l	-----
Typ 20	900 mm	77 mm	1000 mm	-----	1831,9 W	1,330	35,40 kg	4,120 m <sup>2</sup>	9,700 l	-----
Typ 30	900 mm	158 mm	1000 mm	-----	2577,8 W	1,330	51,60 kg	6,170 m <sup>2</sup>	13,400 l	-----

#### Hygiene ECO

Erstellt am 19. Sep. 16

Typ 10	300 mm	47 mm	1000 mm	-----	423,5 W	1,280	6,17 kg	0,680 m <sup>2</sup>	1,890 l	-----
Typ 20	300 mm	77 mm	1000 mm	-----	731,8 W	1,270	11,57 kg	1,370 m <sup>2</sup>	3,710 l	-----
Typ 30	300 mm	158 mm	1000 mm	-----	1090,3 W	1,300	17,80 kg	2,040 m <sup>2</sup>	5,500 l	-----
Typ 10	400 mm	47 mm	1000 mm	-----	539,8 W	1,290	8,22 kg	0,910 m <sup>2</sup>	2,340 l	-----
Typ 20	400 mm	77 mm	1000 mm	-----	917,3 W	1,280	15,35 kg	1,830 m <sup>2</sup>	4,710 l	-----
Typ 30	400 mm	158 mm	1000 mm	-----	1350,6 W	1,300	23,27 kg	2,730 m <sup>2</sup>	7,070 l	-----
Typ 10	500 mm	47 mm	1000 mm	-----	655,1 W	1,300	10,28 kg	1,140 m <sup>2</sup>	2,800 l	-----
Typ 20	500 mm	77 mm	1000 mm	-----	1101,5 W	1,280	19,12 kg	2,280 m <sup>2</sup>	5,700 l	-----
Typ 30	500 mm	158 mm	1000 mm	-----	1603,4 W	1,300	28,73 kg	3,420 m <sup>2</sup>	6,830 l	-----
Typ 10	600 mm	47 mm	1000 mm	-----	768,4 W	1,310	12,33 kg	1,370 m <sup>2</sup>	3,250 l	-----
Typ 20	600 mm	77 mm	1000 mm	-----	1284,2 W	1,290	22,90 kg	2,740 m <sup>2</sup>	6,700 l	-----
Typ 30	600 mm	158 mm	1000 mm	-----	1851,8 W	1,310	34,20 kg	4,110 m <sup>2</sup>	10,200 l	-----
Typ 10	700 mm	47 mm	1000 mm	-----	882,1 W	1,320	14,19 kg	1,600 m <sup>2</sup>	3,770 l	-----
Typ 20	700 mm	77 mm	1000 mm	-----	1465,0 W	1,290	26,83 kg	3,200 m <sup>2</sup>	7,570 l	-----
Typ 30	700 mm	158 mm	1000 mm	-----	2089,9 W	1,310	40,10 kg	4,790 m <sup>2</sup>	11,330 l	-----
Typ 10	900 mm	47 mm	1000 mm	-----	1108,7 W	1,330	17,90 kg	2,060 m <sup>2</sup>	4,800 l	-----
Typ 20	900 mm	77 mm	1000 mm	-----	1833,5 W	1,300	34,70 kg	4,120 m <sup>2</sup>	9,300 l	-----

	Typ	Bauhöhe	Bautiefe	Länge	Reg.-Nr.	Leistung	Exponent	Gewicht	Fläche	Inhalt	Zeta
	Typ 30	900 mm	158 mm	1000 mm	-----	2566,9 W	1,320	51,90 kg	6,170 m <sup>2</sup>	13,600 l	-----
<b>Hygiene ECO Galva</b>									<b>Erstellt am 19. Sep. 16</b>		
	Typ 10	300 mm	47 mm	1000 mm	-----	423,6 W	1,280	6,17 kg	0,680 m <sup>2</sup>	1,890 l	-----
	Typ 20	300 mm	77 mm	1000 mm	-----	731,8 W	1,270	11,57 kg	1,370 m <sup>2</sup>	3,710 l	-----
	Typ 30	300 mm	158 mm	1000 mm	-----	1090,3 W	1,300	17,80 kg	2,040 m <sup>2</sup>	5,500 l	-----
	Typ 10	400 mm	47 mm	1000 mm	-----	539,8 W	1,290	8,22 kg	0,910 m <sup>2</sup>	2,340 l	-----
	Typ 20	400 mm	77 mm	1000 mm	-----	917,3 W	1,280	15,35 kg	1,830 m <sup>2</sup>	4,710 l	-----
	Typ 30	400 mm	158 mm	1000 mm	-----	1350,6 W	1,300	23,27 kg	2,730 m <sup>2</sup>	7,070 l	-----
	Typ 10	500 mm	47 mm	1000 mm	-----	655,2 W	1,300	10,28 kg	1,140 m <sup>2</sup>	2,800 l	-----
	Typ 20	500 mm	77 mm	1000 mm	-----	1101,5 W	1,280	19,12 kg	2,280 m <sup>2</sup>	5,700 l	-----
	Typ 30	500 mm	158 mm	1000 mm	-----	1603,4 W	1,300	28,73 kg	3,420 m <sup>2</sup>	8,630 l	-----
	Typ 10	600 mm	47 mm	1000 mm	-----	768,5 W	1,310	12,33 kg	1,370 m <sup>2</sup>	3,250 l	-----
	Typ 20	600 mm	77 mm	1000 mm	-----	1284,2 W	1,290	22,90 kg	2,740 m <sup>2</sup>	6,700 l	-----
	Typ 30	600 mm	158 mm	1000 mm	-----	1851,9 W	1,310	34,20 kg	4,110 m <sup>2</sup>	10,200 l	-----
	Typ 10	700 mm	47 mm	1000 mm	-----	882,2 W	1,320	14,19 kg	1,600 m <sup>2</sup>	3,770 l	-----
	Typ 20	700 mm	77 mm	1000 mm	-----	1465,0 W	1,290	26,83 kg	3,200 m <sup>2</sup>	7,570 l	-----
	Typ 30	700 mm	158 mm	1000 mm	-----	2090,0 W	1,310	40,10 kg	4,790 m <sup>2</sup>	11,330 l	-----
	Typ 10	900 mm	47 mm	1000 mm	-----	1108,7 W	1,330	17,90 kg	2,060 m <sup>2</sup>	4,800 l	-----
	Typ 20	900 mm	77 mm	1000 mm	-----	1833,5 W	1,300	34,70 kg	4,120 m <sup>2</sup>	9,300 l	-----
	Typ 30	900 mm	158 mm	1000 mm	-----	2566,9 W	1,320	51,90 kg	6,170 m <sup>2</sup>	13,600 l	-----
<b>Hygiene Galva</b>									<b>Erstellt am 19. Sep. 16</b>		
	Typ 10	300 mm	47 mm	1000 mm	-----	423,6 W	1,280	6,17 kg	0,680 m <sup>2</sup>	1,890 l	-----
	Typ 20	300 mm	77 mm	1000 mm	-----	723,2 W	1,340	11,64 kg	1,370 m <sup>2</sup>	3,700 l	-----
	Typ 30	300 mm	158 mm	1000 mm	-----	1080,3 W	1,300	17,90 kg	2,040 m <sup>2</sup>	5,200 l	-----
	Typ 10	400 mm	47 mm	1000 mm	-----	539,8 W	1,290	8,22 kg	0,910 m <sup>2</sup>	2,340 l	-----
	Typ 20	400 mm	77 mm	1000 mm	-----	922,9 W	1,330	15,86 kg	1,830 m <sup>2</sup>	4,670 l	-----

Typ	Bauhöhe	Bautiefe	Länge	Reg.-Nr.	Leistung	Exponent	Gewicht	Fläche	Inhalt	Zeta
Typ 30	400 mm	158 mm	1000 mm	-----	1349,4 W	1,300	23,37 kg	2,730 m <sup>2</sup>	6,570 l	-----
Typ 10	500 mm	47 mm	1000 mm	-----	655,2 W	1,300	10,28 kg	1,140 m <sup>2</sup>	2,800 l	-----
Typ 20	500 mm	77 mm	1000 mm	-----	1114,4 W	1,320	20,08 kg	2,280 m <sup>2</sup>	5,630 l	-----
Typ 30	500 mm	158 mm	1000 mm	-----	1608,8 W	1,310	28,83 kg	3,420 m <sup>2</sup>	7,930 l	-----
Typ 10	600 mm	47 mm	1000 mm	-----	768,5 W	1,310	12,33 kg	1,370 m <sup>2</sup>	3,250 l	-----
Typ 20	600 mm	77 mm	1000 mm	-----	1301,1 W	1,320	24,30 kg	2,740 m <sup>2</sup>	6,600 l	-----
Typ 30	600 mm	158 mm	1000 mm	-----	1856,9 W	1,310	34,30 kg	4,110 m <sup>2</sup>	9,300 l	-----
Typ 10	700 mm	47 mm	1000 mm	-----	882,2 W	1,320	14,19 kg	1,600 m <sup>2</sup>	3,770 l	-----
Typ 20	700 mm	77 mm	1000 mm	-----	1481,6 W	1,320	28,00 kg	3,200 m <sup>2</sup>	7,630 l	-----
Typ 30	700 mm	158 mm	1000 mm	-----	2102,5 W	1,320	40,07 kg	4,790 m <sup>2</sup>	10,670 l	-----
Typ 10	900 mm	47 mm	1000 mm	-----	1108,7 W	1,330	17,90 kg	2,060 m <sup>2</sup>	4,800 l	-----
Typ 20	900 mm	77 mm	1000 mm	-----	1831,9 W	1,330	35,40 kg	4,120 m <sup>2</sup>	9,700 l	-----
Typ 30	900 mm	158 mm	1000 mm	-----	2577,8 W	1,330	51,60 kg	6,170 m <sup>2</sup>	13,400 l	-----

**Nabro**

**Erstellt am 19. Sep. 16**

Nabro	500 mm	121 mm	983 mm	-----	938,5 W	1,340	25,50 kg	2,240 m <sup>2</sup>	8,500 l	-----
Nabro	500 mm	121 mm	1911 mm	-----	1819,9 W	1,340	49,50 kg	4,360 m <sup>2</sup>	16,500 l	-----
Nabro	500 mm	121 mm	1795 mm	-----	1709,7 W	1,340	46,50 kg	4,090 m <sup>2</sup>	15,500 l	-----
Nabro	500 mm	121 mm	1563 mm	-----	1489,4 W	1,340	40,50 kg	3,560 m <sup>2</sup>	13,500 l	-----
Nabro	500 mm	121 mm	1447 mm	-----	1379,2 W	1,340	37,50 kg	3,300 m <sup>2</sup>	12,500 l	-----
Nabro	500 mm	121 mm	1215 mm	-----	1158,8 W	1,340	31,50 kg	2,770 m <sup>2</sup>	10,500 l	-----
Nabro	500 mm	121 mm	751 mm	-----	716,8 W	1,340	19,50 kg	1,720 m <sup>2</sup>	6,500 l	-----
Nabro	500 mm	121 mm	867 mm	-----	827,0 W	1,340	22,50 kg	1,980 m <sup>2</sup>	7,500 l	-----
Nabro	500 mm	121 mm	635 mm	-----	606,6 W	1,340	16,50 kg	1,450 m <sup>2</sup>	5,500 l	-----
Nabro	600 mm	121 mm	1215 mm	-----	1333,6 W	1,340	36,96 kg	3,150 m <sup>2</sup>	12,180 l	-----
Nabro	600 mm	121 mm	1563 mm	-----	1714,8 W	1,340	47,52 kg	4,050 m <sup>2</sup>	15,660 l	-----
Nabro	600 mm	121 mm	1447 mm	-----	1588,2 W	1,340	44,00 kg	3,750 m <sup>2</sup>	14,500 l	-----
Nabro	600 mm	121 mm	1795 mm	-----	1969,4 W	1,340	54,56 kg	4,650 m <sup>2</sup>	17,980 l	-----

Typ	Bauhöhe	Bautiefe	Länge	Reg.-Nr.	Leistung	Exponent	Gewicht	Fläche	Inhalt	Zeta
Nabro	600 mm	121 mm	867 mm	-----	952,4 W	1,340	26,40 kg	2,250 m <sup>2</sup>	8,700 l	-----
Nabro	600 mm	121 mm	751 mm	-----	825,7 W	1,340	22,88 kg	1,950 m <sup>2</sup>	7,540 l	-----
Nabro	600 mm	121 mm	635 mm	-----	699,1 W	1,340	19,36 kg	1,650 m <sup>2</sup>	6,380 l	-----
Nabro	600 mm	121 mm	983 mm	-----	1080,3 W	1,340	29,92 kg	2,550 m <sup>2</sup>	9,860 l	-----
Nabro	600 mm	121 mm	1911 mm	-----	2096,0 W	1,340	58,08 kg	4,950 m <sup>2</sup>	19,140 l	-----

**Novello**

**Erstellt am 19. Sep. 16**

Typ 11	300 mm	61 mm	1000 mm	-----	642,4 W	1,320	9,31 kg	2,090 m <sup>2</sup>	1,890 l	-----
Typ 21	300 mm	77 mm	1000 mm	-----	941,9 W	1,330	14,29 kg	2,440 m <sup>2</sup>	3,700 l	-----
Typ 22	300 mm	100 mm	1000 mm	-----	1241,5 W	1,330	16,80 kg	3,510 m <sup>2</sup>	3,700 l	-----
Typ 33	300 mm	158 mm	1000 mm	-----	1699,5 W	1,310	25,20 kg	5,260 m <sup>2</sup>	5,400 l	-----
Typ 11	400 mm	61 mm	1000 mm	-----	851,6 W	1,310	12,78 kg	2,950 m <sup>2</sup>	2,340 l	-----
Typ 22	400 mm	100 mm	1000 mm	-----	1574,0 W	1,330	22,87 kg	4,920 m <sup>2</sup>	4,670 l	-----
Typ 33	400 mm	158 mm	1000 mm	-----	2159,3 W	1,320	34,30 kg	7,380 m <sup>2</sup>	6,870 l	-----
Typ 11	500 mm	61 mm	1000 mm	-----	1047,6 W	1,300	16,24 kg	3,800 m <sup>2</sup>	2,800 l	-----
Typ 21	500 mm	77 mm	1000 mm	-----	1460,2 W	1,340	24,63 kg	4,310 m <sup>2</sup>	5,630 l	-----
Typ 22	500 mm	100 mm	1000 mm	-----	1888,8 W	1,330	28,93 kg	6,330 m <sup>2</sup>	5,630 l	-----
Typ 33	500 mm	158 mm	1000 mm	-----	2594,7 W	1,320	43,40 kg	9,490 m <sup>2</sup>	8,330 l	-----
Typ 11	600 mm	61 mm	1000 mm	-----	1230,3 W	1,290	19,70 kg	4,660 m <sup>2</sup>	3,250 l	-----
Typ 21	600 mm	77 mm	1000 mm	-----	1703,4 W	1,340	29,80 kg	5,240 m <sup>2</sup>	6,600 l	-----
Typ 22	600 mm	100 mm	1000 mm	-----	2189,7 W	1,330	35,00 kg	7,740 m <sup>2</sup>	6,600 l	-----
Typ 33	600 mm	158 mm	1000 mm	-----	3015,0 W	1,320	52,50 kg	11,610 m <sup>2</sup>	9,800 l	-----
Typ 11	900 mm	61 mm	1000 mm	-----	1707,3 W	1,290	29,30 kg	7,220 m <sup>2</sup>	4,800 l	-----
Typ 21	900 mm	77 mm	1000 mm	-----	2384,8 W	1,340	43,90 kg	8,050 m <sup>2</sup>	9,700 l	-----
Typ 22	900 mm	100 mm	1000 mm	-----	3038,6 W	1,350	51,60 kg	11,970 m <sup>2</sup>	9,700 l	-----
Typ 33	900 mm	158 mm	1000 mm	-----	4244,8 W	1,370	77,30 kg	17,960 m <sup>2</sup>	14,500 l	-----

	Typ	Bauhöhe	Bautiefe	Länge	Reg.-Nr.	Leistung	Exponent	Gewicht	Fläche	Inhalt	Zeta
<b>Novello ECO</b>									<b>Erstellt am 19. Sep. 16</b>		
	Typ 11	300 mm	61 mm	1000 mm	-----	642,3 W	1,320	9,31 kg	2,090 m <sup>2</sup>	1,890 l	-----
	Typ 21	300 mm	77 mm	1000 mm	-----	932,3 W	1,280	14,30 kg	2,440 m <sup>2</sup>	3,800 l	-----
	Typ 22	300 mm	100 mm	1000 mm	-----	1175,3 W	1,310	16,50 kg	3,510 m <sup>2</sup>	3,700 l	-----
	Typ 33	300 mm	158 mm	1000 mm	-----	1702,9 W	1,330	24,70 kg	5,260 m <sup>2</sup>	5,200 l	-----
	Typ 11	400 mm	61 mm	1000 mm	-----	851,6 W	1,310	12,78 kg	2,950 m <sup>2</sup>	2,340 l	-----
	Typ 21	400 mm	77 mm	1000 mm	-----	1163,7 W	1,290	18,83 kg	3,370 m <sup>2</sup>	4,800 l	-----
	Typ 22	400 mm	100 mm	1000 mm	-----	1475,1 W	1,300	21,83 kg	4,920 m <sup>2</sup>	4,770 l	-----
	Typ 33	400 mm	158 mm	1000 mm	-----	2131,5 W	1,330	32,63 kg	7,380 m <sup>2</sup>	6,800 l	-----
	Typ 11	500 mm	61 mm	1000 mm	-----	1047,5 W	1,300	16,24 kg	3,800 m <sup>2</sup>	2,800 l	-----
	Typ 21	500 mm	77 mm	1000 mm	-----	1392,1 W	1,300	23,37 kg	4,310 m <sup>2</sup>	5,800 l	-----
	Typ 22	500 mm	100 mm	1000 mm	-----	1761,8 W	1,300	27,17 kg	6,330 m <sup>2</sup>	5,830 l	-----
	Typ 33	500 mm	158 mm	1000 mm	-----	2537,3 W	1,330	40,57 kg	9,490 m <sup>2</sup>	8,400 l	-----
	Typ 11	600 mm	61 mm	1000 mm	-----	1230,2 W	1,290	19,70 kg	4,660 m <sup>2</sup>	3,250 l	-----
	Typ 21	600 mm	77 mm	1000 mm	-----	1618,4 W	1,300	27,90 kg	5,240 m <sup>2</sup>	6,800 l	-----
	Typ 22	600 mm	100 mm	1000 mm	-----	2033,4 W	1,300	32,50 kg	7,740 m <sup>2</sup>	6,900 l	-----
	Typ 33	600 mm	158 mm	1000 mm	-----	2924,1 W	1,330	48,50 kg	11,610 m <sup>2</sup>	10,000 l	-----
	Typ 11	700 mm	61 mm	1000 mm	-----	1402,2 W	1,290	22,90 kg	5,510 m <sup>2</sup>	3,770 l	-----
	Typ 21	700 mm	77 mm	1000 mm	-----	1848,1 W	1,310	32,70 kg	6,180 m <sup>2</sup>	7,570 l	-----
	Typ 22	700 mm	100 mm	1000 mm	-----	2293,8 W	1,300	38,07 kg	9,150 m <sup>2</sup>	7,630 l	-----
	Typ 33	700 mm	158 mm	1000 mm	-----	3295,8 W	1,330	57,00 kg	13,720 m <sup>2</sup>	11,250 l	-----
	Typ 11	900 mm	61 mm	1000 mm	-----	1707,2 W	1,290	29,30 kg	7,220 m <sup>2</sup>	4,800 l	-----
	Typ 21	900 mm	77 mm	1000 mm	-----	2317,0 W	1,320	42,30 kg	8,050 m <sup>2</sup>	9,100 l	-----
	Typ 22	900 mm	100 mm	1000 mm	-----	2791,8 W	1,300	49,20 kg	11,970 m <sup>2</sup>	9,100 l	-----
	Typ 33	900 mm	158 mm	1000 mm	-----	4020,2 W	1,330	74,00 kg	17,960 m <sup>2</sup>	13,750 l	-----
<b>Novello Plinth</b>									<b>Erstellt am 19. Sep. 16</b>		
	Typ 22	200 mm	100 mm	1000 mm	-----	818,6 W	1,300	9,67 kg	2,050 m <sup>2</sup>	2,830 l	-----



	Typ	Bauhöhe	Bautiefe	Länge	Reg.-Nr.	Leistung	Exponent	Gewicht	Fläche	Inhalt	Zeta
	Typ 33	200 mm	158 mm	1000 mm	-----	1171,2 W	1,290	15,40 kg	3,080 m <sup>2</sup>	4,200 l	-----
	Typ 44	200 mm	216 mm	1000 mm	-----	1524,1 W	1,300	20,80 kg	4,100 m <sup>2</sup>	5,600 l	-----

**Planar**

Erstellt am 19. Sep. 16

	22	300 mm	102 mm	1000 mm	-----	1168,2 W	1,300	19,60 kg	3,510 m <sup>2</sup>	3,700 l	-----
	33	300 mm	160 mm	1000 mm	-----	1695,6 W	1,310	28,00 kg	5,260 m <sup>2</sup>	5,400 l	-----
	11	400 mm	63 mm	1000 mm	-----	785,8 W	1,290	16,13 kg	2,950 m <sup>2</sup>	2,340 l	-----
	22	400 mm	102 mm	1000 mm	-----	1480,1 W	1,300	26,40 kg	4,920 m <sup>2</sup>	4,670 l	-----
	33	400 mm	160 mm	1000 mm	-----	2132,8 W	1,320	38,13 kg	7,380 m <sup>2</sup>	6,870 l	-----
	11	500 mm	63 mm	1000 mm	-----	969,9 W	1,280	20,39 kg	3,800 m <sup>2</sup>	2,800 l	-----
	21	500 mm	79 mm	1000 mm	-----	1340,2 W	1,320	28,89 kg	4,310 m <sup>2</sup>	5,630 l	-----
	22	500 mm	102 mm	1000 mm	-----	1777,5 W	1,310	33,20 kg	6,330 m <sup>2</sup>	5,630 l	-----
	33	500 mm	160 mm	1000 mm	-----	2549,9 W	1,330	48,27 kg	9,490 m <sup>2</sup>	8,330 l	-----
	11	600 mm	63 mm	1000 mm	-----	1139,6 W	1,270	24,65 kg	4,660 m <sup>2</sup>	3,250 l	-----
	21	600 mm	79 mm	1000 mm	-----	1548,4 W	1,320	34,90 kg	5,240 m <sup>2</sup>	6,600 l	-----
	22	600 mm	102 mm	1000 mm	-----	2062,1 W	1,320	40,00 kg	7,740 m <sup>2</sup>	6,600 l	-----
	33	600 mm	160 mm	1000 mm	-----	2953,4 W	1,340	58,40 kg	11,610 m <sup>2</sup>	9,800 l	-----
	11	700 mm	63 mm	1000 mm	-----	1300,7 W	1,280	28,91 kg	5,510 m <sup>2</sup>	3,770 l	-----
	21	700 mm	79 mm	1000 mm	-----	1750,4 W	1,320	40,91 kg	6,180 m <sup>2</sup>	7,630 l	-----
	22	700 mm	102 mm	1000 mm	-----	2336,3 W	1,330	46,80 kg	9,150 m <sup>2</sup>	7,630 l	-----
	33	700 mm	160 mm	1000 mm	-----	3339,6 W	1,340	68,53 kg	13,720 m <sup>2</sup>	11,370 l	-----
	11	900 mm	63 mm	1000 mm	-----	1581,7 W	1,290	37,43 kg	7,220 m <sup>2</sup>	4,800 l	-----
	21	900 mm	79 mm	1000 mm	-----	2129,0 W	1,310	52,94 kg	8,050 m <sup>2</sup>	9,700 l	-----
	22	900 mm	102 mm	1000 mm	-----	2855,8 W	1,350	60,40 kg	11,970 m <sup>2</sup>	9,700 l	-----
	33	900 mm	160 mm	1000 mm	-----	4084,3 W	1,340	88,80 kg	17,960 m <sup>2</sup>	14,500 l	-----

**Planar ECO**

Erstellt am 19. Sep. 16

	22	300 mm	102 mm	1000 mm	-----	1109,6 W	1,270	18,85 kg	3,510 m <sup>2</sup>	2,900 l	-----
--	----	--------	--------	---------	-------	----------	-------	----------	----------------------	---------	-------

Typ	Bauhöhe	Bautiefe	Länge	Reg.-Nr.	Leistung	Exponent	Gewicht	Fläche	Inhalt	Zeta
33	300 mm	160 mm	1000 mm	-----	1586,1 W	1,310	26,45 kg	5,260 m <sup>2</sup>	4,350 l	-----
11	400 mm	79 mm	1000 mm	-----	785,9 W	1,290	16,13 kg	2,950 m <sup>2</sup>	2,340 l	-----
21	400 mm	102 mm	1000 mm	-----	1110,3 W	1,280	21,95 kg	3,370 m <sup>2</sup>	4,110 l	-----
22	400 mm	102 mm	1000 mm	-----	1399,8 W	1,280	24,95 kg	4,920 m <sup>2</sup>	3,880 l	-----
33	400 mm	160 mm	1000 mm	-----	2002,8 W	1,320	35,12 kg	7,380 m <sup>2</sup>	5,820 l	-----
21	500 mm	79 mm	1000 mm	-----	1324,2 W	1,300	27,28 kg	4,310 m <sup>2</sup>	4,930 l	-----
11	500 mm	79 mm	1000 mm	-----	969,9 W	1,280	20,39 kg	3,800 m <sup>2</sup>	2,800 l	-----
22	500 mm	102 mm	1000 mm	-----	1673,4 W	1,290	31,05 kg	6,330 m <sup>2</sup>	4,870 l	-----
33	500 mm	160 mm	1000 mm	-----	2401,7 W	1,350	43,78 kg	9,490 m <sup>2</sup>	7,280 l	-----
21	600 mm	79 mm	1000 mm	-----	1519,2 W	1,300	32,60 kg	5,240 m <sup>2</sup>	5,750 l	-----
11	600 mm	79 mm	1000 mm	-----	1139,6 W	1,270	24,65 kg	4,660 m <sup>2</sup>	3,250 l	-----
22	600 mm	102 mm	1000 mm	-----	1929,5 W	1,290	37,15 kg	7,740 m <sup>2</sup>	5,850 l	-----
33	600 mm	160 mm	1000 mm	-----	2765,8 W	1,350	52,45 kg	11,610 m <sup>2</sup>	8,750 l	-----
11	700 mm	79 mm	1000 mm	-----	1300,8 W	1,280	28,91 kg	5,510 m <sup>2</sup>	3,770 l	-----
21	700 mm	79 mm	1000 mm	-----	1698,5 W	1,290	37,85 kg	6,180 m <sup>2</sup>	6,630 l	-----
22	700 mm	102 mm	1000 mm	-----	2178,1 W	1,300	42,82 kg	9,150 m <sup>2</sup>	6,730 l	-----
33	700 mm	160 mm	1000 mm	-----	3105,4 W	1,340	61,13 kg	13,720 m <sup>2</sup>	10,190 l	-----
21	900 mm	79 mm	1000 mm	-----	2028,7 W	1,290	48,35 kg	8,050 m <sup>2</sup>	8,400 l	-----
11	900 mm	79 mm	1000 mm	-----	1581,8 W	1,290	37,43 kg	7,220 m <sup>2</sup>	4,800 l	-----
22	900 mm	102 mm	1000 mm	-----	2640,5 W	1,310	54,15 kg	11,970 m <sup>2</sup>	8,500 l	-----
33	900 mm	160 mm	1000 mm	-----	3738,6 W	1,340	78,50 kg	17,960 m <sup>2</sup>	13,060 l	-----

**Planar Plinth**

**Erstellt am 19. Sep. 16**

Typ 22	200 mm	102 mm	1000 mm	-----	762,9 W	1,260	12,30 kg	2,050 m <sup>2</sup>	2,800 l	-----
Typ 33	200 mm	160 mm	1000 mm	-----	1150,3 W	1,280	17,60 kg	3,080 m <sup>2</sup>	4,200 l	-----
Typ 44	200 mm	218 mm	1000 mm	-----	1502,6 W	1,290	23,00 kg	4,100 m <sup>2</sup>	5,600 l	-----

	Typ	Bauhöhe	Bautiefe	Länge	Reg.-Nr.	Leistung	Exponent	Gewicht	Fläche	Inhalt	Zeta
<b>Planar Plinth D</b>											
									<b>Erstellt am 19. Sep. 16</b>		
	Typ 22	200 mm	104 mm	1000 mm	-----	720,5 W	1,270	13,50 kg	2,050 m <sup>2</sup>	2,800 l	-----
	Typ 33	200 mm	162 mm	1000 mm	-----	1131,3 W	1,260	19,30 kg	3,080 m <sup>2</sup>	4,200 l	-----
	Typ 44	200 mm	220 mm	1000 mm	-----	1479,9 W	1,280	24,60 kg	4,100 m <sup>2</sup>	5,600 l	-----
<b>Planar Slim ECO</b>											
									<b>Erstellt am 19. Sep. 16</b>		
	21	545 mm	96 mm	1000 mm	-----	1287,7 W	1,300	29,31 kg	4,310 m <sup>2</sup>	5,800 l	-----
	22	545 mm	119 mm	1000 mm	-----	1636,9 W	1,290	32,73 kg	6,330 m <sup>2</sup>	5,830 l	-----
	21	645 mm	96 mm	1000 mm	-----	1491,5 W	1,310	34,80 kg	5,240 m <sup>2</sup>	6,800 l	-----
	22	645 mm	119 mm	1000 mm	-----	1883,8 W	1,300	38,80 kg	7,740 m <sup>2</sup>	6,900 l	-----
<b>Planar Style</b>											
									<b>Erstellt am 19. Sep. 16</b>		
	22	300 mm	102 mm	1000 mm	-----	1129,3 W	1,300	19,30 kg	3,510 m <sup>2</sup>	3,100 l	-----
	33	300 mm	160 mm	1000 mm	-----	1618,4 W	1,300	27,60 kg	5,260 m <sup>2</sup>	5,400 l	-----
	11	400 mm	63 mm	1000 mm	-----	768,0 W	1,270	16,20 kg	2,950 m <sup>2</sup>	2,300 l	-----
	22	400 mm	102 mm	1000 mm	-----	1449,9 W	1,300	25,67 kg	4,920 m <sup>2</sup>	4,130 l	-----
	33	400 mm	160 mm	1000 mm	-----	2077,4 W	1,310	36,63 kg	7,380 m <sup>2</sup>	6,630 l	-----
	11	500 mm	63 mm	1000 mm	-----	934,8 W	1,280	20,23 kg	3,800 m <sup>2</sup>	2,770 l	-----
	21	500 mm	79 mm	1000 mm	-----	1305,3 W	1,300	28,00 kg	4,310 m <sup>2</sup>	5,200 l	-----
	22	500 mm	102 mm	1000 mm	-----	1748,5 W	1,310	32,03 kg	6,330 m <sup>2</sup>	5,170 l	-----
	33	500 mm	160 mm	1000 mm	-----	2497,5 W	1,320	45,67 kg	9,490 m <sup>2</sup>	7,870 l	-----
	11	600 mm	63 mm	1000 mm	-----	1090,2 W	1,280	24,27 kg	4,660 m <sup>2</sup>	3,230 l	-----
	21	600 mm	79 mm	1000 mm	-----	1506,7 W	1,310	33,60 kg	5,240 m <sup>2</sup>	6,250 l	-----
	22	600 mm	102 mm	1000 mm	-----	2016,9 W	1,310	38,40 kg	7,740 m <sup>2</sup>	6,200 l	-----
	33	600 mm	160 mm	1000 mm	-----	2877,4 W	1,320	54,70 kg	11,610 m <sup>2</sup>	9,100 l	-----
	11	700 mm	63 mm	1000 mm	-----	1236,8 W	1,280	28,30 kg	5,510 m <sup>2</sup>	3,700 l	-----
	21	700 mm	79 mm	1000 mm	-----	1700,7 W	1,310	39,20 kg	6,180 m <sup>2</sup>	7,300 l	-----
	22	700 mm	102 mm	1000 mm	-----	2266,5 W	1,320	44,70 kg	9,150 m <sup>2</sup>	7,030 l	-----

Typ	Bauhöhe	Bautiefe	Länge	Reg.-Nr.	Leistung	Exponent	Gewicht	Fläche	Inhalt	Zeta
33	700 mm	160 mm	1000 mm	-----	3227,6 W	1,330	63,60 kg	13,720 m <sup>2</sup>	10,630 l	-----
11	900 mm	63 mm	1000 mm	-----	1503,7 W	1,280	35,90 kg	7,220 m <sup>2</sup>	4,500 l	-----
21	900 mm	79 mm	1000 mm	-----	2081,0 W	1,320	50,60 kg	8,050 m <sup>2</sup>	9,000 l	-----
22	900 mm	102 mm	1000 mm	-----	2690,6 W	1,320	57,30 kg	11,970 m <sup>2</sup>	8,700 l	-----
33	900 mm	160 mm	1000 mm	-----	3820,5 W	1,330	81,40 kg	17,960 m <sup>2</sup>	13,700 l	-----

### Planar Style ECO

Erstellt am 19. Sep. 16

22	300 mm	102 mm	1000 mm	-----	1109,5 W	1,270	18,85 kg	3,510 m <sup>2</sup>	2,900 l	-----
33	300 mm	160 mm	1000 mm	-----	1586,0 W	1,310	26,45 kg	5,260 m <sup>2</sup>	4,350 l	-----
21	400 mm	79 mm	1000 mm	-----	1110,2 W	1,280	21,95 kg	3,370 m <sup>2</sup>	4,110 l	-----
22	400 mm	102 mm	1000 mm	-----	1399,7 W	1,280	24,95 kg	4,920 m <sup>2</sup>	3,880 l	-----
33	400 mm	160 mm	1000 mm	-----	2002,8 W	1,320	35,12 kg	7,380 m <sup>2</sup>	5,820 l	-----
21	500 mm	79 mm	1000 mm	-----	1324,2 W	1,300	27,28 kg	4,310 m <sup>2</sup>	4,930 l	-----
22	500 mm	102 mm	1000 mm	-----	1673,3 W	1,290	31,05 kg	6,330 m <sup>2</sup>	4,870 l	-----
33	500 mm	160 mm	1000 mm	-----	2401,6 W	1,350	43,78 kg	9,490 m <sup>2</sup>	7,280 l	-----
21	600 mm	79 mm	1000 mm	-----	1519,1 W	1,300	32,60 kg	5,240 m <sup>2</sup>	5,750 l	-----
22	600 mm	102 mm	1000 mm	-----	1929,4 W	1,290	37,15 kg	7,740 m <sup>2</sup>	5,850 l	-----
33	600 mm	160 mm	1000 mm	-----	2765,7 W	1,350	52,45 kg	11,610 m <sup>2</sup>	8,750 l	-----
21	700 mm	79 mm	1000 mm	-----	1698,5 W	1,290	37,85 kg	6,180 m <sup>2</sup>	6,630 l	-----
22	700 mm	102 mm	1000 mm	-----	2178,1 W	1,300	42,82 kg	9,150 m <sup>2</sup>	6,730 l	-----
33	700 mm	160 mm	1000 mm	-----	3105,3 W	1,340	61,13 kg	13,720 m <sup>2</sup>	10,190 l	-----
21	900 mm	79 mm	1000 mm	-----	2028,6 W	1,290	48,35 kg	8,050 m <sup>2</sup>	8,400 l	-----
22	900 mm	102 mm	1000 mm	-----	2640,5 W	1,310	54,15 kg	11,970 m <sup>2</sup>	8,500 l	-----
33	900 mm	160 mm	1000 mm	-----	3738,6 W	1,340	78,50 kg	17,960 m <sup>2</sup>	13,060 l	-----

### Planar Style Plinth

Erstellt am 19. Sep. 16

Typ 22	200 mm	102 mm	1000 mm	-----	762,9 W	1,260	12,30 kg	2,050 m <sup>2</sup>	2,800 l	-----
Typ 33	200 mm	160 mm	1000 mm	-----	1150,3 W	1,280	17,60 kg	3,080 m <sup>2</sup>	4,200 l	-----

	Typ	Bauhöhe	Bautiefe	Länge	Reg.-Nr.	Leistung	Exponent	Gewicht	Fläche	Inhalt	Zeta
	Typ 44	200 mm	218 mm	1000 mm	-----	1502,6 W	1,290	23,00 kg	4,100 m <sup>2</sup>	5,600 l	-----
<b>Planar Style Plinth D</b>										<b>Erstellt am 19. Sep. 16</b>	
	Typ 22	200 mm	104 mm	1000 mm	-----	720,5 W	1,270	13,50 kg	2,050 m <sup>2</sup>	2,800 l	-----
	Typ 33	200 mm	162 mm	1000 mm	-----	1131,3 W	1,260	19,30 kg	3,080 m <sup>2</sup>	4,200 l	-----
	Typ 44	200 mm	220 mm	1000 mm	-----	1479,9 W	1,280	24,60 kg	4,100 m <sup>2</sup>	5,600 l	-----
<b>Reno Compact</b>										<b>Erstellt am 19. Sep. 16</b>	
	Typ 22	400 mm	100 mm	1000 mm	-----	1574,0 W	1,330	22,87 kg	4,920 m <sup>2</sup>	4,670 l	-----
	Typ 33	400 mm	158 mm	1000 mm	-----	2159,3 W	1,320	34,30 kg	7,380 m <sup>2</sup>	6,870 l	-----
	Typ 21	550 mm	77 mm	1000 mm	-----	1583,1 W	1,340	27,21 kg	4,780 m <sup>2</sup>	5,940 l	-----
	Typ 22	550 mm	100 mm	1000 mm	-----	2040,5 W	1,330	31,97 kg	7,040 m <sup>2</sup>	6,120 l	-----
	Typ 33	550 mm	158 mm	1000 mm	-----	2806,7 W	1,320	47,95 kg	10,550 m <sup>2</sup>	9,070 l	-----
	Typ 21	950 mm	77 mm	1000 mm	-----	2409,7 W	1,330	45,00 kg	8,520 m <sup>2</sup>	10,100 l	-----
	Typ 22	950 mm	100 mm	1000 mm	-----	3047,1 W	1,340	53,50 kg	12,680 m <sup>2</sup>	10,050 l	-----
	Typ 33	950 mm	158 mm	1000 mm	-----	4340,2 W	1,340	78,00 kg	19,020 m <sup>2</sup>	15,300 l	-----
<b>Valeriana</b>										<b>Erstellt am 19. Sep. 16</b>	
	Valeriana	775 mm	50 mm	495 mm	-----	457,4 W	1,250	6,00 kg	0,640 m <sup>2</sup>	3,600 l	-----
	Valeriana	775 mm	60 mm	585 mm	-----	530,7 W	1,260	6,89 kg	0,740 m <sup>2</sup>	4,010 l	-----
	Valeriana	775 mm	70 mm	737 mm	-----	648,2 W	1,250	8,40 kg	0,910 m <sup>2</sup>	4,700 l	-----
	Valeriana	1181 mm	50 mm	495 mm	-----	675,5 W	1,260	9,00 kg	0,970 m <sup>2</sup>	5,400 l	-----
	Valeriana	1181 mm	60 mm	585 mm	-----	781,5 W	1,250	10,23 kg	1,120 m <sup>2</sup>	6,030 l	-----
	Valeriana	1181 mm	70 mm	737 mm	-----	957,3 W	1,250	12,30 kg	1,370 m <sup>2</sup>	7,100 l	-----
	Valeriana	1763 mm	50 mm	495 mm	-----	1009,5 W	1,270	13,40 kg	1,450 m <sup>2</sup>	8,000 l	-----
	Valeriana	1763 mm	60 mm	585 mm	-----	1168,3 W	1,270	15,26 kg	1,680 m <sup>2</sup>	8,970 l	-----
	Valeriana	1763 mm	70 mm	737 mm	-----	1429,8 W	1,260	18,40 kg	2,060 m <sup>2</sup>	10,600 l	-----

	Typ	Bauhöhe	Bautiefe	Länge	Reg.-Nr.	Leistung	Exponent	Gewicht	Fläche	Inhalt	Zeta
<b>Valeriana CT</b>											<b>Erstellt am 19. Sep. 16</b>
	Valeriana CT	775 mm	50 mm	495 mm	-----	457,4 W	1,250	6,00 kg	0,640 m <sup>2</sup>	3,600 l	-----
	Valeriana CT	775 mm	60 mm	585 mm	-----	530,7 W	1,260	6,89 kg	0,740 m <sup>2</sup>	4,010 l	-----
	Valeriana CT	775 mm	70 mm	737 mm	-----	648,2 W	1,250	8,40 kg	0,910 m <sup>2</sup>	4,700 l	-----
	Valeriana CT	1181 mm	50 mm	495 mm	-----	675,5 W	1,260	9,00 kg	0,970 m <sup>2</sup>	5,400 l	-----
	Valeriana CT	1181 mm	60 mm	585 mm	-----	781,5 W	1,250	10,23 kg	1,120 m <sup>2</sup>	6,030 l	-----
	Valeriana CT	1181 mm	70 mm	737 mm	-----	957,3 W	1,250	12,30 kg	1,370 m <sup>2</sup>	7,100 l	-----
	Valeriana CT	1763 mm	50 mm	495 mm	-----	1009,5 W	1,270	13,40 kg	1,450 m <sup>2</sup>	8,000 l	-----
	Valeriana CT	1763 mm	60 mm	585 mm	-----	1168,3 W	1,270	15,26 kg	1,680 m <sup>2</sup>	8,970 l	-----
	Valeriana CT	1763 mm	70 mm	737 mm	-----	1429,8 W	1,260	18,40 kg	2,060 m <sup>2</sup>	10,600 l	-----
<b>Vertex</b>											<b>Erstellt am 19. Sep. 16</b>
	11	1600 mm	47 mm	1000 mm	6R1133	2731,8 W	1,340	42,90 kg	9,400 m <sup>2</sup>	7,200 l	-----
	10	1600 mm	47 mm	1000 mm	6R1132	2097,8 W	1,270	30,90 kg	3,670 m <sup>2</sup>	7,200 l	-----
	20	1600 mm	77 mm	1000 mm	6R1134	3271,1 W	1,320	63,30 kg	7,330 m <sup>2</sup>	14,400 l	-----
	21	1600 mm	77 mm	1000 mm	6R1135	3823,9 W	1,320	71,10 kg	12,660 m <sup>2</sup>	14,100 l	-----
	22	1600 mm	100 mm	1000 mm	6R1136	4589,2 W	1,330	80,70 kg	28,990 m <sup>2</sup>	14,100 l	-----
	11	1800 mm	47 mm	1000 mm	6R1133	3007,6 W	1,330	48,30 kg	9,860 m <sup>2</sup>	8,400 l	-----
	10	1800 mm	47 mm	1000 mm	6R1132	2338,7 W	1,290	34,50 kg	4,130 m <sup>2</sup>	8,400 l	-----
	21	1800 mm	77 mm	1000 mm	6R1135	4209,9 W	1,330	80,10 kg	13,580 m <sup>2</sup>	16,500 l	-----
	20	1800 mm	77 mm	1000 mm	6R1134	3609,3 W	1,310	71,10 kg	8,250 m <sup>2</sup>	16,200 l	-----
	22	1800 mm	100 mm	1000 mm	6R1136	5006,4 W	1,330	88,80 kg	29,900 m <sup>2</sup>	16,200 l	-----
	11	2000 mm	47 mm	1000 mm	6R1133	3280,7 W	1,330	53,70 kg	12,150 m <sup>2</sup>	9,300 l	-----
	10	2000 mm	47 mm	1000 mm	6R1132	2588,0 W	1,300	38,10 kg	4,590 m <sup>2</sup>	9,300 l	-----
	21	2000 mm	77 mm	1000 mm	6R1135	4551,3 W	1,330	89,10 kg	16,200 m <sup>2</sup>	18,600 l	-----
	20	2000 mm	77 mm	1000 mm	6R1134	3930,6 W	1,310	78,60 kg	9,170 m <sup>2</sup>	18,000 l	-----
	22	2000 mm	100 mm	1000 mm	6R1136	5423,6 W	1,330	96,60 kg	37,740 m <sup>2</sup>	18,000 l	-----
	10	2200 mm	47 mm	1000 mm	6R1132	2858,4 W	1,320	42,00 kg	5,040 m <sup>2</sup>	10,200 l	-----

Typ	Bauhöhe	Bautiefe	Länge	Reg.-Nr.	Leistung	Exponent	Gewicht	Fläche	Inhalt	Zeta
11	2200 mm	47 mm	1000 mm	6R1133	3536,2 W	1,320	57,90 kg	12,610 m <sup>2</sup>	10,200 l	-----
20	2200 mm	77 mm	1000 mm	6R1134	4263,2 W	1,300	87,60 kg	10,090 m <sup>2</sup>	20,100 l	-----
21	2200 mm	77 mm	1000 mm	6R1135	4892,6 W	1,330	98,40 kg	17,110 m <sup>2</sup>	20,100 l	-----
22	2200 mm	100 mm	1000 mm	6R1136	5851,1 W	1,340	108,90 kg	38,660 m <sup>2</sup>	20,100 l	-----

### Vertex Plan

Erstellt am 19. Sep. 16

11	1600 mm	49 mm	1000 mm	6R1133	2467,9 W	1,310	56,10 kg	9,400 m <sup>2</sup>	7,200 l	-----
20	1600 mm	79 mm	1000 mm	6R1134	2889,7 W	1,270	77,70 kg	7,330 m <sup>2</sup>	14,100 l	-----
21	1600 mm	79 mm	1000 mm	6R1135	3537,5 W	1,310	85,80 kg	12,660 m <sup>2</sup>	14,100 l	-----
22	1600 mm	102 mm	1000 mm	6R1136	4316,1 W	1,320	94,20 kg	28,990 m <sup>2</sup>	14,100 l	-----
11	1800 mm	49 mm	1000 mm	6R1133	2682,4 W	1,300	63,00 kg	9,860 m <sup>2</sup>	8,100 l	-----
20	1800 mm	79 mm	1000 mm	6R1134	3167,4 W	1,270	86,70 kg	8,250 m <sup>2</sup>	16,200 l	-----
21	1800 mm	79 mm	1000 mm	6R1135	3848,2 W	1,300	96,00 kg	13,580 m <sup>2</sup>	15,900 l	-----
22	1800 mm	102 mm	1000 mm	6R1136	4665,1 W	1,330	105,30 kg	29,900 m <sup>2</sup>	15,900 l	-----
11	2000 mm	49 mm	1000 mm	6R1133	2889,9 W	1,300	69,60 kg	12,150 m <sup>2</sup>	9,000 l	-----
20	2000 mm	79 mm	1000 mm	6R1134	3437,6 W	1,270	95,40 kg	9,170 m <sup>2</sup>	18,300 l	-----
21	2000 mm	79 mm	1000 mm	6R1135	4112,3 W	1,300	106,20 kg	16,200 m <sup>2</sup>	17,700 l	-----
22	2000 mm	102 mm	1000 mm	6R1136	5006,4 W	1,330	116,40 kg	37,740 m <sup>2</sup>	17,700 l	-----
11	2200 mm	49 mm	1000 mm	6R1133	3080,7 W	1,290	75,60 kg	12,610 m <sup>2</sup>	9,900 l	-----
21	2200 mm	79 mm	1000 mm	6R1135	4414,1 W	1,300	116,40 kg	17,110 m <sup>2</sup>	20,100 l	-----
20	2200 mm	79 mm	1000 mm	6R1134	3700,3 W	1,270	105,60 kg	10,090 m <sup>2</sup>	20,100 l	-----
22	2200 mm	102 mm	1000 mm	6R1136	5347,8 W	1,330	126,60 kg	38,660 m <sup>2</sup>	20,100 l	-----

### Vertex Slim

Erstellt am 19. Sep. 16

11	1840 mm	73 mm	670 mm	-----	1609,4 W	1,300	37,80 kg	5,920 m <sup>2</sup>	4,900 l	-----
11	1840 mm	73 mm	470 mm	-----	1072,9 W	1,300	25,20 kg	3,940 m <sup>2</sup>	3,200 l	-----
11	1840 mm	73 mm	570 mm	-----	1341,2 W	1,300	31,50 kg	4,930 m <sup>2</sup>	4,100 l	-----
21	1840 mm	96 mm	670 mm	-----	2308,9 W	1,300	57,60 kg	8,150 m <sup>2</sup>	9,500 l	-----

Typ	Bauhöhe	Bautiefe	Länge	Reg.-Nr.	Leistung	Exponent	Gewicht	Fläche	Inhalt	Zeta
21	1840 mm	96 mm	570 mm	-----	1924,0 W	1,300	48,00 kg	6,790 m <sup>2</sup>	8,000 l	-----
21	1840 mm	96 mm	470 mm	-----	1539,2 W	1,300	38,40 kg	5,430 m <sup>2</sup>	6,400 l	-----
22	1840 mm	119 mm	670 mm	-----	2799,0 W	1,330	63,20 kg	17,940 m <sup>2</sup>	9,500 l	-----
22	1840 mm	119 mm	570 mm	-----	2332,5 W	1,330	52,70 kg	14,950 m <sup>2</sup>	8,000 l	-----
22	1840 mm	119 mm	470 mm	-----	1866,0 W	1,330	42,10 kg	11,960 m <sup>2</sup>	6,400 l	-----
11	2040 mm	73 mm	670 mm	-----	1733,9 W	1,300	41,80 kg	7,290 m <sup>2</sup>	5,400 l	-----
11	2040 mm	73 mm	570 mm	-----	1444,9 W	1,300	34,80 kg	6,080 m <sup>2</sup>	4,500 l	-----
11	2040 mm	73 mm	470 mm	-----	1155,9 W	1,300	27,80 kg	4,860 m <sup>2</sup>	3,600 l	-----
21	2040 mm	96 mm	470 mm	-----	1644,9 W	1,300	42,50 kg	6,480 m <sup>2</sup>	7,100 l	-----
21	2040 mm	96 mm	670 mm	-----	2467,3 W	1,300	63,70 kg	9,720 m <sup>2</sup>	10,600 l	-----
21	2040 mm	96 mm	570 mm	-----	2056,1 W	1,300	53,10 kg	8,100 m <sup>2</sup>	8,900 l	-----
22	2040 mm	119 mm	670 mm	-----	3003,8 W	1,330	69,80 kg	22,640 m <sup>2</sup>	10,600 l	-----
22	2040 mm	119 mm	470 mm	-----	2002,5 W	1,330	46,60 kg	15,100 m <sup>2</sup>	7,100 l	-----
22	2040 mm	119 mm	570 mm	-----	2503,2 W	1,330	58,20 kg	18,870 m <sup>2</sup>	8,900 l	-----

### Vertex Style

Erstellt am 19. Sep. 16

11	1600 mm	49 mm	1000 mm	6R1133	2467,9 W	1,310	56,10 kg	9,400 m <sup>2</sup>	7,200 l	-----
20	1600 mm	79 mm	1000 mm	6R1134	2889,7 W	1,270	77,70 kg	7,330 m <sup>2</sup>	14,100 l	-----
21	1600 mm	79 mm	1000 mm	6R1135	3537,5 W	1,310	85,80 kg	12,660 m <sup>2</sup>	14,100 l	-----
22	1600 mm	102 mm	1000 mm	6R1136	4316,1 W	1,320	94,20 kg	28,990 m <sup>2</sup>	14,100 l	-----
11	1800 mm	49 mm	1000 mm	6R1133	2682,4 W	1,300	63,00 kg	9,860 m <sup>2</sup>	8,100 l	-----
21	1800 mm	79 mm	1000 mm	6R1135	3848,2 W	1,300	96,00 kg	13,580 m <sup>2</sup>	15,900 l	-----
20	1800 mm	79 mm	1000 mm	6R1134	3167,4 W	1,270	86,70 kg	8,250 m <sup>2</sup>	16,200 l	-----
22	1800 mm	102 mm	1000 mm	6R1136	4665,1 W	1,330	105,30 kg	29,900 m <sup>2</sup>	15,900 l	-----
11	2000 mm	49 mm	1000 mm	6R1133	2889,9 W	1,300	69,60 kg	12,150 m <sup>2</sup>	9,000 l	-----
20	2000 mm	79 mm	1000 mm	6R1134	3437,6 W	1,270	95,40 kg	9,170 m <sup>2</sup>	18,300 l	-----
21	2000 mm	79 mm	1000 mm	6R1135	4112,3 W	1,300	106,20 kg	16,200 m <sup>2</sup>	17,700 l	-----
22	2000 mm	102 mm	1000 mm	6R1136	5006,4 W	1,330	116,40 kg	37,740 m <sup>2</sup>	17,700 l	-----



Typ	Bauhöhe	Bautiefe	Länge	Reg.-Nr.	Leistung	Exponent	Gewicht	Fläche	Inhalt	Zeta
11	2200 mm	49 mm	1000 mm	6R1133	3080,7 W	1,290	75,60 kg	12,610 m <sup>2</sup>	9,900 l	-----
20	2200 mm	79 mm	1000 mm	6R1134	3700,3 W	1,270	105,60 kg	10,090 m <sup>2</sup>	20,100 l	-----
21	2200 mm	79 mm	1000 mm	6R1135	4414,1 W	1,300	116,40 kg	17,110 m <sup>2</sup>	20,100 l	-----
22	2200 mm	102 mm	1000 mm	6R1136	5347,8 W	1,330	126,60 kg	38,660 m <sup>2</sup>	20,100 l	-----

### Vertex Swing

Erstellt am 19. Sep. 16

11	1820 mm	73 mm	681 mm	-----	1609,4 W	1,300	37,80 kg	5,920 m <sup>2</sup>	4,900 l	-----
11	1820 mm	73 mm	481 mm	-----	1072,9 W	1,300	25,20 kg	3,940 m <sup>2</sup>	3,200 l	-----
11	1820 mm	73 mm	581 mm	-----	1341,2 W	1,300	31,50 kg	4,930 m <sup>2</sup>	4,100 l	-----
21	1820 mm	96 mm	704 mm	-----	2308,9 W	1,300	57,60 kg	8,150 m <sup>2</sup>	9,500 l	-----
21	1820 mm	96 mm	604 mm	-----	1924,0 W	1,300	48,00 kg	6,790 m <sup>2</sup>	8,000 l	-----
21	1820 mm	96 mm	504 mm	-----	1539,2 W	1,300	38,40 kg	5,430 m <sup>2</sup>	6,400 l	-----
22	1820 mm	119 mm	627 mm	-----	2332,5 W	1,330	52,70 kg	14,950 m <sup>2</sup>	8,000 l	-----
22	1820 mm	119 mm	727 mm	-----	2799,0 W	1,330	63,20 kg	17,940 m <sup>2</sup>	9,500 l	-----
22	1820 mm	119 mm	527 mm	-----	1866,0 W	1,330	42,10 kg	11,960 m <sup>2</sup>	6,400 l	-----
11	2020 mm	73 mm	681 mm	-----	1733,9 W	1,300	41,80 kg	7,290 m <sup>2</sup>	5,400 l	-----
11	2020 mm	73 mm	581 mm	-----	1444,9 W	1,300	34,80 kg	6,080 m <sup>2</sup>	4,500 l	-----
11	2020 mm	73 mm	481 mm	-----	1155,9 W	1,300	27,80 kg	4,860 m <sup>2</sup>	3,600 l	-----
21	2020 mm	96 mm	704 mm	-----	2467,3 W	1,300	63,70 kg	9,720 m <sup>2</sup>	10,600 l	-----
21	2020 mm	96 mm	604 mm	-----	2056,1 W	1,300	53,10 kg	8,100 m <sup>2</sup>	8,900 l	-----
21	2020 mm	96 mm	504 mm	-----	1644,9 W	1,300	42,50 kg	6,480 m <sup>2</sup>	7,100 l	-----
22	2020 mm	119 mm	727 mm	-----	3003,8 W	1,330	69,80 kg	22,640 m <sup>2</sup>	10,600 l	-----
22	2020 mm	119 mm	527 mm	-----	2002,5 W	1,330	46,60 kg	15,100 m <sup>2</sup>	7,100 l	-----
22	2020 mm	119 mm	627 mm	-----	2503,2 W	1,330	58,20 kg	18,870 m <sup>2</sup>	8,900 l	-----

### Vertex Tango

Erstellt am 19. Sep. 16

11	1820 mm	73 mm	410 mm	-----	1072,9 W	1,300	25,20 kg	3,940 m <sup>2</sup>	3,200 l	-----
11	1820 mm	73 mm	510 mm	-----	1341,2 W	1,300	31,50 kg	4,930 m <sup>2</sup>	4,100 l	-----

Typ	Bauhöhe	Bautiefe	Länge	Reg.-Nr.	Leistung	Exponent	Gewicht	Fläche	Inhalt	Zeta
11	1820 mm	73 mm	610 mm	-----	1609,4 W	1,300	37,80 kg	5,920 m <sup>2</sup>	4,900 l	-----
21	1820 mm	96 mm	610 mm	-----	2308,9 W	1,300	57,60 kg	8,150 m <sup>2</sup>	9,500 l	-----
21	1820 mm	96 mm	410 mm	-----	1539,2 W	1,300	38,40 kg	5,430 m <sup>2</sup>	6,400 l	-----
21	1820 mm	96 mm	510 mm	-----	1924,0 W	1,300	48,00 kg	6,790 m <sup>2</sup>	8,000 l	-----
22	1820 mm	119 mm	610 mm	-----	2799,0 W	1,330	63,20 kg	17,940 m <sup>2</sup>	9,500 l	-----
22	1820 mm	119 mm	510 mm	-----	2332,5 W	1,330	52,70 kg	14,950 m <sup>2</sup>	8,000 l	-----
22	1820 mm	119 mm	410 mm	-----	1866,0 W	1,330	42,10 kg	11,960 m <sup>2</sup>	6,400 l	-----
11	2020 mm	73 mm	510 mm	-----	1444,9 W	1,300	34,80 kg	6,080 m <sup>2</sup>	4,500 l	-----
11	2020 mm	73 mm	410 mm	-----	1155,9 W	1,300	27,80 kg	4,860 m <sup>2</sup>	3,600 l	-----
11	2020 mm	73 mm	610 mm	-----	1733,9 W	1,300	41,80 kg	7,290 m <sup>2</sup>	5,400 l	-----
21	2020 mm	96 mm	410 mm	-----	1644,9 W	1,300	42,50 kg	6,480 m <sup>2</sup>	7,100 l	-----
21	2020 mm	96 mm	610 mm	-----	2467,3 W	1,300	63,70 kg	9,720 m <sup>2</sup>	10,600 l	-----
21	2020 mm	96 mm	510 mm	-----	2056,1 W	1,300	53,10 kg	8,100 m <sup>2</sup>	8,900 l	-----
22	2020 mm	119 mm	410 mm	-----	2002,5 W	1,330	46,60 kg	15,100 m <sup>2</sup>	7,100 l	-----
22	2020 mm	119 mm	510 mm	-----	2503,2 W	1,330	58,20 kg	18,870 m <sup>2</sup>	8,900 l	-----
22	2020 mm	119 mm	610 mm	-----	3003,8 W	1,330	69,80 kg	22,640 m <sup>2</sup>	10,600 l	-----

**Vertical Galva**

**Erstellt am 19. Sep. 16**

10	1600 mm	47 mm	1000 mm	-----	2097,8 W	1,270	30,90 kg	3,670 m <sup>2</sup>	7,200 l	-----
11	1600 mm	47 mm	1000 mm	-----	2731,8 W	1,340	42,90 kg	9,400 m <sup>2</sup>	7,200 l	-----
20	1600 mm	77 mm	1000 mm	-----	3271,1 W	1,320	63,30 kg	7,330 m <sup>2</sup>	14,400 l	-----
21	1600 mm	77 mm	1000 mm	-----	3823,9 W	1,320	71,70 kg	12,660 m <sup>2</sup>	14,100 l	-----
22	1600 mm	100 mm	1000 mm	-----	4589,2 W	1,330	80,70 kg	28,990 m <sup>2</sup>	14,100 l	-----
10	1800 mm	47 mm	1000 mm	-----	2338,7 W	1,290	34,50 kg	4,130 m <sup>2</sup>	8,400 l	-----
11	1800 mm	47 mm	1000 mm	-----	3007,6 W	1,330	48,30 kg	9,860 m <sup>2</sup>	8,400 l	-----
20	1800 mm	77 mm	1000 mm	-----	3609,3 W	1,310	71,10 kg	8,250 m <sup>2</sup>	16,200 l	-----
21	1800 mm	77 mm	1000 mm	-----	4209,9 W	1,330	80,10 kg	13,580 m <sup>2</sup>	16,500 l	-----
22	1800 mm	100 mm	1000 mm	-----	5006,4 W	1,330	88,80 kg	29,900 m <sup>2</sup>	16,200 l	-----

Typ	Bauhöhe	Bautiefe	Länge	Reg.-Nr.	Leistung	Exponent	Gewicht	Fläche	Inhalt	Zeta
11	2000 mm	47 mm	1000 mm	-----	3280,7 W	1,330	53,70 kg	12,150 m <sup>2</sup>	9,300 l	-----
10	2000 mm	47 mm	1000 mm	-----	2588,1 W	1,300	38,10 kg	4,590 m <sup>2</sup>	9,300 l	-----
20	2000 mm	77 mm	1000 mm	-----	3930,6 W	1,310	78,60 kg	9,170 m <sup>2</sup>	18,000 l	-----
21	2000 mm	77 mm	1000 mm	-----	4551,3 W	1,330	89,10 kg	16,200 m <sup>2</sup>	18,600 l	-----
22	2000 mm	100 mm	1000 mm	-----	5423,6 W	1,330	96,60 kg	37,740 m <sup>2</sup>	18,000 l	-----
10	2200 mm	47 mm	1000 mm	-----	2858,5 W	1,320	42,00 kg	5,040 m <sup>2</sup>	10,200 l	-----
11	2200 mm	47 mm	1000 mm	-----	3536,2 W	1,320	57,90 kg	12,610 m <sup>2</sup>	10,200 l	-----
20	2200 mm	77 mm	1000 mm	-----	4263,2 W	1,300	87,60 kg	10,090 m <sup>2</sup>	20,100 l	-----
21	2200 mm	77 mm	1000 mm	-----	4892,6 W	1,330	98,40 kg	17,110 m <sup>2</sup>	20,100 l	-----
22	2200 mm	100 mm	1000 mm	-----	5851,1 W	1,340	108,90 kg	38,660 m <sup>2</sup>	20,100 l	-----